

CAUTIONS!

CONTAINS XYLOL, METHYL
ISOBUTYL KETONE AND
CUPROUS OXIDE

DO NOT USE, POUR, SPILL OR
STORE NEAR HEAT OR OPEN
FLAME.

Avoid breathing of vapor or spray
mist.

Avoid contact with skin.

Do not take internally.

Close container after using.

Do not reuse empty container.

Destroy it by perforating or crush-
ing. Bury or discard in a safe
place.

FIRST AID: If swallowed, do NOT
induce vomiting.

CALL A PHYSICIAN.

USE WITH
ADEQUATE VENTILATION

DEVVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

BOOTTOP ANTI-FOULING COATING

MD-3273

WARNING!

KEEP OUT OF REACH OF CHILDREN

**COMBUSTIBLE — VAPOR HARMFUL
HARMFUL OR FATAL IF SWALLOWED**

5 U. S. GALLONS

Read Carefully Cautions on Left Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY
E.P.A. REG. NO. 9461-37

ACTIVE INGREDIENTS

Cuprous Oxide 40.08%*

INERT INGREDIENTS 59.92%

100.00%

*Equivalent to 34.4%
Metallic Copper

BATCH NO

Directions For Use

Be sure that all surfaces are clean,
free of moisture, scale, grease or
oil. Remove all loose paint with
wire brush or scraper. Mix thor-
oughly; both by stirring and then
pouring from one clean container
to another several times. Stir from
time to time during application.

Apply one or two coats "as is" on
ship bottoms by brush or roller.
For spraying, thin if necessary with
MD-1931 Devian Thinner. Do not
add oil or varnishes to this paint.
Allow four hours between coats.

Anti-fouling paints must be applied
over suitable barrier coats and
should not be applied directly to
metal. Vessels may be launched
anytime after two hours at 77
degrees F under good conditions.

MAF 3273 683B 7-21-71

A PRODUCT OF

**DEVVOE & RAYNOLDS
COMPANY, INC.**

NEWARK, NEW JERSEY 07105

NEW ORLEANS, LA. 70117

SAN FRANCISCO, CALIF. 94104