

ACCEPTED  
9/11/82

# DEVON<sup>®</sup>

## MARINE

**PAINTS & COATINGS • WORLD-WIDE**

FORMULA 213

MD-1968 DEVVAN<sup>®</sup>

**RED ANTI-FOULING SHIP BOTTOM COATING**

ACTIVE INGREDIENTS	
Copper Comp.	30.22% *
NON-INGREDIENTS	03.78%
	<u>100.00%</u>

**WARNING**

KEEP OUT OF REACH OF CHILDREN  
COMBUSTIBLE - VAPOR HARMFUL  
HARMFUL OR FATAL IF SWALLOWED

\*Equivalent to 31.1%  
Metallic Copper.

← 18 pt.

**U.S. GALLONS** FOR INDUSTRY USE BY PROFESSIONAL APPLICATORS ONLY

## DIRECTIONS FOR USE

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly both by stirring and then pouring. Allow to settle for 10 minutes before use. Stir from time to time during application.

Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with DEVRAN<sup>®</sup> MO-194. Do not add oil or varnish to this paint. Allow 4 hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Vessels may be launched anytime after 2 hours at 77° F. under good conditions.

### CAUTIONS!

CONTAINS XYLOL, METHYL ISOBUTYL KETONE AND CUPROUS OXIDE

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.

Avoid breathing of vapor or spray mist.

Avoid contact with skin.

Do not take internally.

Close container after using.

Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place.

FIRST AID: If swallowed, do NOT induce vomiting.

CALL A PHYSICIAN.

USE WITH ADEQUATE VENTILATION

A Product of  
**DEVOE & RAYNOLDS CO., INC.**  
Newark, N. J. • San Francisco, California • New Orleans, La.  
97105 94104 70117

ACCEPTED

8/11/11

## DIRECTIONS FOR USE

Remove all loose material, free of moisture, scale, rust, etc. Remove all former paint with wire brush or scrape. Mix thoroughly with by stirring and then pouring.

Use with adequate ventilation.

Apply over the "old" coat on ship bottoms by brush or spray. Apply over "old" coat on steel structures by brush or spray. Apply over "old" coat on steel structures by brush or spray. Apply over "old" coat on steel structures by brush or spray.

Do not apply directly to metal. Vessels may be painted anytime after 2 hours at 77° F. under good conditions.

CONTINUED

CONTAINMENT, STORAGE, TRANSPORT, ETC. SEE THE CONTAINER LABEL.

DO NOT USE, IN OR OUT OF THE CONTAINER, IF THE CONTAINER IS DAMAGED.  
Avoid breathing vapors. Avoid contact with skin and eyes.  
Use adequate ventilation.  
Close container immediately after use.  
Do not use in confined spaces. Do not use in areas where fire or explosion is a hazard.  
FIRST AID: If swallowed, induce vomiting. If inhaled, get fresh air. If on skin, wash with water. If in eyes, flush with water. CALL A PHYSICIAN.

USE WITH ADEQUATE VENTILATION

A Product of  
**DEVCO & RAYNOLDS CO., INC.**  
Newark, N. J. • San Francisco, California • New Orleans, La.  
98103 • 94107 • 70117

REGISTERED