

DEVOE

MARINE

PAINTS & COATINGS · WORLD-WIDE

**VYKING (VINYL)
ANTI-FOULING
MD-883
WARNING**

KEEP OUT OF REACH OF CHILDREN

5 U. S. GALLONS VAPOR HARMFUL—COMBUSTIBLE

Read Carefully Cautions on Back Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY
USDA REG. NO. 9461-49

ACTIVE INGREDIENTS	48.3%
Cuprous Oxide	51.7%
INERT INGREDIENTS	100.0%

BATCH NO.

© D & R CO. 1963

DIRECTIONS FOR USE

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly both by stirring and then pouring from one clean container to another several times. Stir from time to time during application.

Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with DEVRAN® MD-1931 Thinner. Do not add oil or varnishes to this paint. Allow 4 hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Vessels may be launched anytime after 2 hours at 77° F. under good conditions.

CAUTION

CONTAINS AROMATIC HYDROCARBONS AND KETONES

Keep away from heat and open flame. Avoid breathing of vapor or spray mist. Avoid contact with skin. Do not take internally. Close container after using.

USE WITH ADEQUATE VENTILATION

MUD VAF 8/1/69

A Product of

DEVOE & RAYNOLDS CO., INC.

Newark, N. J. — New Orleans, La. — San Francisco, Calif.
07105 70117 94104

ACCEPTED
FOR THE MARINE USE
OF THE U.S. NAVY
UNDER THE
MILITARY AND NAVAL
CONTRACTS ADMINISTRATION
AGREEMENT

DEVOE[®] MARINE

PAINTS & COATINGS · WORLD-WIDE

**VYKING (VINYL)
ANTI-FOULING
MD-883
WARNING**

KEEP OUT OF REACH OF CHILDREN

5 U. S. GALLONS VAPOR HARMFUL—COMBUSTIBLE

Read Carefully Cautions on Back Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY
USDA REG. NO. 9461-49

ACTIVE INGREDIENTS
Cuprous Oxide 48.75
INERT INGREDIENTS 51.25
100.00

BATCH #

© 1963 DEVOE

DIRECTIONS FOR USE

Be sure that all surfaces are clean, free of dirt, grease, oil, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, test on test panel, and then apply from one clean container to another, stirring contents time to time during application.

Apply one or two coats with brush, roller, or spray roller. For spraying, thin to one coat with Devolve Thinner. Do not let the paint dry for this period. Wait 4 hours between coats.

Anti-Fouling paint is not to be applied to the hull of a boat and should not be applied to the hull of a boat which has been launched and is intended for use in salt water conditions.

CAUTION

CONTAINS AROMATIC HYDROCARBONS AND KETONES

Keep away from heat, open flame, sparks, and other sources of ignition. Vapor may irritate eyes, nose, throat, and lungs. Use outdoors only.

USE WITH ADEQUATE VENTILATION

MD-883 (100)

A Product of

DEVOE & RAYNOLDS CO., INC.

Swindon, England New Orleans, La. St. Francisco, Calif.