

DEVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

MUD MAF 3260 1/1/70

9461-52

ANTI-FOULING MD-3260

ACCEPTED
 Feb 3, 1971
 UNDER THE FEDERAL INSECTICIDE
 FUNGICIDE AND ROENTGEN RAY ACT
 FOR ECONOMIC PESTICIDE REGISTRATION
 UNDER NO.

WARNING

KEEP OUT OF REACH OF CHILDREN

**VAPOR HARMFUL-COMBUSTIBLE
HARMFUL IF SWALLOWED**

See Antidote on Rear Panel
Read Carefully Cautions on Back Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY

USDA REG. NO. 9461-52

ACTIVE INGREDIENTS	
Cuprous Oxide	24.59%
Bis (Tri-n-butyltin) Oxide	1.86%
Pentachlorophenol	2.00%
Related Chlorophenols	.23%
INERT INGREDIENTS	71.32%
	100.00%

BATCH NO.

5 U.S. GALLONS

DIRECTIONS FOR USE

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container to another several times. Stir from time to time during application.

Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with Thinner MD-342. Do not add oil or varnishes to this paint. Allow 4 hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Launching may be accomplished as soon as one hour after the final application but not later than 24 hours after final application.

CAUTION

**CONTAINS AROMATIC HYDROCARBONS, PHENOL AND
BIS (TRI-n-BUTYLTIN) OXIDE**

Keep away from heat, sparks and open flame. Avoid breathing of vapor or spray mist. May be absorbed through skin. Causes skin irritation. Avoid contact with skin, eyes or clothing. In case of contact, remove contaminated clothing and wash skin with soap and water; for eyes, flush with plenty of water and get medical attention. Wash clothing before reuse. Avoid storage near feed and food products. Do not take internally. Close container after each use.

USE WITH ADEQUATE VENTILATION

ANTIDOTE: Give a tablespoon of salt in a glass of warm water and repeat until vomit fluid is clear. Then two tablespoons of Epsom Salt or Milk of Magnesia in water and force fluids. Have patient lie down and keep quiet. CALL A PHYSICIAN.

MUD MAF TBTO 10/1/70

A Product of
DEVOE & RAYNOLDS CO., INC.
Newark, N. J. • San Francisco, California • New Orleans, La.
07105 94104 70117

DEVOLÉ[®] MARINE

PAINTS & COATINGS WORLD-WIDE

ANTI-FOULING MD-3260

WARNING

KEEP OUT OF REACH OF CHILDREN

VAPOR HARMFUL-COMBUSTIBLE
HARMFUL IF SWALLOWED

3 U.S. GALLONS

See Instructions on Rear Panel
Read Carefully the Data on Back Panel
APPLIED BY PROFESSIONAL APPLICATORS ONLY
DO NOT MIX WITH OTHERS

DIRECTIONS FOR USE

For application of this product, refer to the instructions on the back panel of the container. The product is to be applied to the hull of the vessel, and the surface must be clean, dry, and free of any oil or grease. The product is to be applied in a thin, uniform coat, and the surface must be allowed to dry for 24 hours before the vessel is launched. The product is to be reapplied as directed on the back panel of the container.

CAUTION

CONTAINS AROMATIC HYDROCARBONS, PHENOL AND
BIS (TRI n-BUTYL TIN) OXIDE

Keep away from children. Do not use in confined spaces. Avoid contact with skin and eyes. If contact occurs, wash thoroughly with water. Do not breathe vapors. Use with adequate ventilation.

USE WITH ADEQUATE VENTILATION

ANTIDOTE

None known.