

DEVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

ACCEPTED
3-3-72
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC PEACE REGISTRY
EPA REG. NO. 461-54

ANTI-FOULING MD-3198
DANGER!

KEEP OUT OF REACH OF CHILDREN

VAPOR HARMFUL - COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED
MAY CAUSE SEVERE EYE BURNS
AND SKIN IRRITATION

ANTI-FOULING INGREDIENTS
Active Ingredients
Tri-n-Butyltin Fluoride 13.80%
Inert Ingredients 86.20%
100.00%

Read Carefully Caution on Left Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY
E.P.A. REG. NO. 9461-54

5 U.S. GALLONS

BATCH NO.

ACCEPTED
3-3-72
UNDER THE FEDERAL INSECTICIDE
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC PEACE REGISTRY
EPA REG. NO. 461-54
DANGER!

**CONTAINS TRI-n-BUTYL TIN
FLUORIDE, GLYCOL ETHER
AND KETONES**

Keep away from heat and open flame. Avoid breathing of vapor or spray mist. Do not get in eyes, on skin or clothing. Personnel spraying this paint should wear full face air mask and protective clothing to avoid skin and eye contact. May be absorbed through skin. In case of contact, immediately remove contaminated clothing and wash skin with soap and water. For eyes, flush with plenty of water and get immediate medical attention. Wash clothing before reuse. Do not take internally. Close container after using. Avoid storage near feed or feedstuffs.

**USE WITH ADEQUATE
VENTILATION**

Directions For Use

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container to another several times. Stir from time to time during application. Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with THINNER MD-1931. Do not add oil or varnishes to this paint. Allow four hours between coats. Anti-fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Launching may be accomplished as soon as one hour after the final application but not later than 24 hours after final application.

MAF 3198/610B 4/19/71

A PRODUCT OF
**DEVOE & RAYNOLDS
COMPANY, INC.**
NEWARK, NEW JERSEY 07105
NEW ORLEANS, LA. 70117
SAN FRANCISCO, CALIF. 94104

DEVORE®

MARINE

PAINTS & COATINGS - WORLD-WIDE

MADE IN U.S.A.
100-00

ANTI-FOULING MD-3198

DANGER!

KEEP OUT OF REACH OF CHILDREN

**VAPOR HARMFUL - COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED
MAY CAUSE SEVERE EYE BURNS
AND SKIN IRRITATION**

Read Carefully Cautions on Left Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY
E.P.A. REG. NO. 9451-54

ANTI-FOULING INGREDIENTS
Active Ingredients
Tri-n-Butyltin Fluoride 17.5%
Inert Ingredients 86.4%
100.0%

BATCH NO.

5 U.S. GALLONS

ACCEPTED

DANGER!

**CONTAINS TRI-n-BUTYLTIN
FLUORIDE, GLYCOL ETHER
AND KETONES**

Keep away from heat and open flame. Avoid breathing of vapor or spray mist. Do not get in eyes, on skin or clothing. Personnel spraying this paint should wear full face air mask and protective clothing to avoid skin and eye contact. May be absorbed through skin. In case of contact, immediately remove contaminated clothing and wash skin with soap and water. For eyes, flush with plenty of water and get immediate medical attention. Wash clothing before reuse. Do not take internally. Close container after using. Avoid storage near feed or feedstuff.

**USE WITH ADEQUATE
VENTILATION**

Directions For Use

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container to another several times. Stir from time to time during application. Apply one or two coats, as is on ship bottoms by brush or roller. For spraying, thin, if necessary, with THINNER MD-1921. Do not add oil or varnishes to this paint. Allow four hours between coats. Anti-fouling paints must be applied over suitable primer coats, and should not be used on surfaces of metal. Touching may be accomplished as soon as the paint after the final application, but not less than 24 hours after the final application.

A PRODUCT OF
**DEVORE & RAYNOLDS
COMPANY, INC.**

NEWARK, NEW JERSEY 07102
NEW ORLEANS, LA 70117
SAN FRANCISCO, CALIF. 94104