

DANGER!

**CONTAINS LEAD, XYLOL AND
TRI-n-BUTYL TIN ACETATE**

**DO NOT USE, POUR, SPILL OR
STAY NEAR HEAT OR OPEN
FLAME.**

**Avoid breathing of vapor or spray
mist.**

Do not take internally.

**May be absorbed through skin.
Causes skin irritation.**

**Avoid contact with skin, eyes or
clothing.**

**Avoid storage near food and food
products.**

**Close container after using. Do not
reuse empty container; destroy it
by perforating or crushing and
bury or discard in a safe place.**

**FIRST AID: if swallowed, induce
vomiting. CALL A PHYSICIAN.**

**In case of skin contact remove con-
taminated clothing and wash skin
with soap and water; for eyes,
flush with plenty of water and get
medical attention. Wash clothing
before reuse.**

**USE WITH ADEQUATE
VENTILATION**

DEVVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

DEVALUM® ANTI-FOULING

MD-3404

DANGER

KEEP OUT OF REACH OF CHILDREN

HARMFUL OR FATAL IF SWALLOWED

VAPOR HARMFUL - COMBUSTIBLE

MAY CAUSE EYE OR SKIN IRRITATION

5 U. S. GALLONS

**Read Carefully Caution on Left Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY**

L.P.A. REG. NO. 841726

**ANTI-FOULING INGREDIENTS
ACTIVE INGREDIENTS
Tri-n-butyltin Acetate
INERT INGREDIENTS**

**0.07%
99.91%
100.00%**

BATCH NO.

Directions For Use

Be sure that all surfaces are clean,
free of moisture, scale, grease or
oil. Remove all loose paint with
wire brush or scraper. Mix thor-
oughly, both by stirring and then
pouring from one clean container
to another several times. Stir from
time to time during application.

Apply one or two coats "as is" on
ship bottoms by brush or roller. For
spraying, thin if necessary with
Thinner MD-542. Do not add oil or
varnishes to this paint. Allow 4
hours between coats.

Anti-Fouling paints must be applied
over suitable barrier coats and
should not be applied directly to
metal. Launching may be accom-
plished as soon as one hour after
the final application but not later
than 24 hours after final appli-
cation.

MAF 3404/696 11/11/71

**A PRODUCT OF
DEVVOE & RAYNOLDS
COMPANY, INC.
NEWARK, NEW JERSEY 07108
NEW ORLEANS, LA. 70117
SAN FRANCISCO, CALIF. 94104**

DANGER!

**CONTAINS LEAD, XYLOL AND
TRI-n-BUTYLTIN ACETATE**

**DO NOT USE, POUR, SPILL OR
STORE NEAR HEAT OR OPEN
FLAME.**

**Avoid breathing of vapor or spray
mist.**

Do not take internally.

**May be absorbed through skin.
Causes skin irritation.**

**Avoid contact with skin, eyes or
clothing.**

**Avoid storage near feed and food
products.**

**Close container after using. Do not
reuse empty container; destroy it
by perforating or crushing and
bury or discard in a safe place.**

**FIRST AID: If swallowed, induce
vomiting. CALL A PHYSICIAN.**

**In case of skin contact remove con-
taminated clothing and wash skin
with soap and water; for eyes,
flush with plenty of water and get
medical attention. Wash clothing
before reuse.**

**USE WITH ADEQUATE
VENTILATION**

DEVVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

**DEVALUM® ANTI-FOULING
MD-3404
DANGER**

KEEP OUT OF REACH OF CHILDREN

**HARMFUL OR FATAL IF SWALLOWED
VAPOR HARMFUL - COMBUSTIBLE
MAY CAUSE EYE OR SKIN IRRITATION**

ANTI-FOULING INGREDIENTS	
ACTIVE INGREDIENTS	
Tri-n-Butyltin Acetate	9.09%
INERT INGREDIENTS	90.91%
	100.00%

5 U. S. GALLONS

**Read Carefully Cautions on Left Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY**

BATCH NO.

Directions For Use

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container to another several times. Stir from time to time during application.

Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with Thinner MD-542. Do not add oil or varnishes to this paint. Allow 4 hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Launching may be accomplished as soon as one hour after the final application but not later than 24 hours after final application.

MAF 3404/696 11/11/71

**A PRODUCT OF
DEVVOE & RAYNOLDS
COMPANY, INC.**
NEWARK, NEW JERSEY 07105
NEW ORLEANS, LA. 70117
SAN FRANCISCO, CALIF. 94104