

UNION PACIFIC INDUSTRIAL PRODUCTS
777 1/2
CITY

WARNING
CONTAINS
**LEAD, XYLENE AND
BIS (TRIMETHYLH) OXIDE**

DO NOT USE, POUR, SPILL OR
BURN NEAR HEAT OR OPEN
FLAME.

Avoid breathing of vapor or spray
mist.

May be absorbed through skin.
Causes skin irritation.

Avoid contact with skin, eyes or
mucous.

Avoid storage near food and food
products.

Close container after using. Do not
reuse empty container; destroy it
by perforating or crushing and
bury or discard in a safe place.

Do not contaminate water by clean-
ing or equipment or disposal of
waste.

FIRST AID: If swallowed, induce
vomiting. CALL A PHYSICIAN.

In case of skin contact remove con-
taminated clothing and wash skin
with soap and water; for eyes,
flush with plenty of water and get
medical attention. Wash clothing
before reuse.

**USE WITH ADEQUATE
VENTILATION**

DEVALUM

MARINE

PAINTS & COATINGS • WORLD-WIDE

DEVALUM® ANTI-FOUL
MD-340

Sept 28 1978
9461-65

WARNING!
KEEP OUT OF REACH OF CHILDREN
HARMFUL OR FATAL IF SWAL
VAPOR HARMFUL - COMBUS
MAY CAUSE EYE OR SKIN IRRI

1 U.S. GALLONS **Read Carefully Cautions on Left Panel**

ACTIVE INGREDIENTS
XYLENE
BIS (TRIMETHYLH) OXIDE

2.77%
91.57
100.00%

Directions for

Be sure that all surfaces
free of moisture, soil,
oil. Remove all loose
material with scraper,
brush, sandpaper, etc.
Remove from one coat
to the next. Allow time
to dry during applica-
tion. Apply one or two coats
depending on surface
preparation. This is not a
water based paint. Do not
use over old paint.
Do not use over oil.

Anti-fouling paint must
only be applied to hulls
and should not be applied
to deck, including the
plank as soon as possible
after the final application but
not less than 24 hours after
application.

For more information
write to:
Camoramar, Inc.
1000 17th Street
San Francisco, Calif.
94133