

DEVOE[®] MARINE

ANTS & COATINGS · WORLD-WIDE

ANTI-FOULING MD-3408

WARNING

KEEP OUT OF REACH OF CHILDREN

**VAPOR HARMFUL — COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED**

Read Carefully Cautions on Back Panel

ACTIVE INGREDIENTS

Cuprous Oxide	11.70%
NEUTRAL INGREDIENTS	88.28%
	100.00%

BATCH NO.

© D & R CO. 1962

DIRECTIONS FOR USE

Be sure that all surfaces are clean, free of rust, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container into another several times. Stir constantly during application.

Apply one or two coats (as is on ship bottom) by brush or roller. For spraying, thin if necessary with MD 542 Thinner. Do not add oil or varnishes to this paint. Allow 4 hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Launching may be accomplished as soon as one hour after the final application but not later than 24 hours after final application.

WARNING!

CONTAINS XYLCL, BUTYL ALCOHOL AND CUPROUS OXIDE

Keep away from heat and open flame. Avoid breathing of vapor and spray mist. Avoid contact with skin. Do not take internally. Close container after using. **FIRST AID:** If swallowed, do NOT induce vomiting. CALL A PHYSICIAN.

USE WITH ADEQUATE VENTILATION

MAID MAR 3408 10 27 70

A Product of

DEVOE & RAYNOLDS CO., INC.

Newark, N. J.
07102

New Orleans, La.
70117

San Francisco, Calif.
94104

GALLONS

FOR USE BY PROFESSIONAL APPLICATORS ONLY

USDA REG. NO. 9451