

DEVORE

DIRECTIONS FOR USE

Be sure that all surfaces are properly prepared and primed before applying this coating. Agitate from time to time during application. Apply at 300°F. with special Hot Spray Equipment. Use Hi Flash Naphtha for clean-up.

Apply at 300°F. with special hot Spray Equipment.
Use Hi Flash Naphtha for clean-up.

Anti-fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Launching may be accomplished as soon as one hour after the final application but not later than 72 hours after final application.

MARINE

PAINTS & COATINGS • WORLD-WIDE

HOT PLASTIC NO. 15HPN-MIL-P-19452

MD-8140

CAUTION

**KEEP OUT OF REACH OF CHILDREN
HARMFUL IF SWALLOWED**

Read Carefully Cautions on Back Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY

5 U. S. GALLONS

USDA REG. NO. 9461-68

ACTIVE INGREDIENTS	
Cuprous Oxide	32.5%
Copper Linoleate	9.4%
INERT INGREDIENTS	58.1%
	100.0%

BATCH NO.

ACCEPTED
REGISTERED
61-68

ED
REGISTERED
68

CAUTION!

CONTAINS CUPROUS OXIDE

Keep away from open flame. Do not take internally.
Close container after using.

USE WITH ADEQUATE VENTILATION

MUD-MAF 15HPN 10/1/70

A Product of
DEVORE & RAYNOLDS CO., INC.
Newark, N. J. 07105 • San Francisco, California 94104 • New Orleans, La. 70117

REGISTERED WITH COMMENTS

© D & R CO. 1963