

DEVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

WARNING!

CONTAINS XYLOL,
BUTYL ALCOHOL
AND CUPROUS OXIDE

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME. Avoid breathing of vapor or spray mist. Avoid contact with skin. Do not take internally. Close container after using. Do not re-use empty container. Destroy it by perforating or crushing. Bury or discard in a safe place.

FIRST AID: If swallowed, do NOT induce vomiting.
CALL A PHYSICIAN.

USE WITH ADEQUATE
VENTILATION

5 U. S. GALLONS

DEV²23/72
9461-71
DEV[®] FORMULA 216
ANTI-FOULING
MD-3545

WARNING!

KEEP OUT OF THE REACH OF CHILDREN

VAPOR HARMFUL — COMBUSTIBLE
HARMFUL OR FATAL IF SWALLOWED

Read Carefully Warning on Left Panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY
E.P.A. REG. 9461-71

ACTIVE INGREDIENTS
Cuprous Oxide

39.96%*

INERT INGREDIENTS

60.04%

100.00%

*Equivalent to 34.37%
Metallic Copper

BATCH NO

Directions for Use

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container to another several times. Stir from time to time during application.

Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with MD-1931 Thinner. Do not add oil or varnish to this paint. Allow four hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Launching may be accomplished as soon as one hour after the final application.

MAF 216 625A 9 23 71

A PRODUCT OF
**DEVOE & RAYNOLDS
COMPANY, INC.**

NEWARK, NEW JERSEY 07105
NEW ORLEANS, LA. 70117
SAN FRANCISCO, CALIF. 94104