

CAUTION

CONTAINS

**BIS (TRIBUTYL TIN) OXIDE
AND CUPROUS OXIDE**

DO NOT USE, POUR, SPILL OR
STORE NEAR HEAT OR OPEN
FLAME

Avoid breathing of vapor or spray
mist

May be absorbed through skin.
Causes skin irritation.

Avoid contact with skin, eyes or
clothing.

Avoid storage near feed and food
products

Close container after using. Do not
reuse empty container, destroy it
by perforating or crushing and
bury or discard in a safe place.

Do not contaminate water by clean-
ing of equipment or disposal of
waste.

FIRST AID: If swallowed, induce
vomiting. CALL A PHYSICIAN.

In case of skin contact, remove con-
taminated clothing and wash skin
with soap and water. For eyes,
flush with plenty of water and get
medical attention. Wash clothing
before reuse.

USE WITH ADEQUATE

VENTILATION

DEVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

ANTI-FOULING PAINT MD-3694

WARNING

KEEP OUT OF REACH OF CHILDREN
VAPOR HARMFUL — COMBUSTIBLE
HARMFUL IF SWALLOWED

Read carefully cautions on left panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY

E.P.A. REG. NO. 9461-80

ACTIVE INGREDIENTS:
Cuprous Oxide 20.41
Copper Powder 2.52
Bis-Tributyltin Oxide 1.80
INERT INGREDIENTS 75.27

100% Solids
E.P.A. Reg. No. 9461-80
E.P.A. Reg. No. 9461-80

Directions for Use

Be sure that all surfaces are clean,
free of moisture, scale, grease or
oil. Remove all loose paint with
wire brush or scraper. Mix thor-
oughly with the stirring rod then
pouring from one clean container
to another several times. Set aside
time for the drying of paint.

Apply in two coats, as a com-
pact but porous finish. For
spraying, thin it liberally with
MD 542 THINNER. Do not add any
varnish to this paint. Allow four
hours to dry in shade.

Anti-fouling paint may be applied
over suitable primer coats and
should not be applied directly to
metal. It is not recommended for
application on surfaces where
the flow rate of water is less than
2 ft. per second. For applica-
tion.

**DEVOE & RAYNOLDS
COMPANY, INC.**

NEWARK, NEW JERSEY 07105
NEW ORLEANS, LA 70117
SAN FRANCISCO, CALIF 94104

5 U. S. GALLONS