

DEVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

ANTI-FOULING PAINT MD-3696

WARNING

KEEP OUT OF REACH OF CHILDREN
VAPOR HARMFUL — COMBUSTIBLE
HARMFUL IF SWALLOWED

Read carefully cautions on left panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY

E.P.A. REG. NO. 9461-82

ACCEPTED

ACTIVE INGREDIENTS:	
Cuprous Oxide	22.10%
Copper Powder	2.73%
Bis (Tributyltin) Oxide	1.80%
INERT INGREDIENTS	73.37%

100.00

Equivalent to 22.36% Metallic
Copper and 0.71% Metallic Tin

Directions for Use

Be sure that all surfaces are clean, free of moisture, scale, grease, or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container to another several times. Stir from time to time during application.

Apply one or two coats, as is on ship bottoms by brush or roller. For spraying, thin if necessary with MD-542 THINNER. Do not add oil or varnishes to this paint. Allow four hours between coats.

Anti-Fouling paints must be applied over suitable barrier coats and should not be applied directly to metal. Launching may be accomplished as soon as one hour after the final application but not later than 24 hours after final application.

DEVOE & RAYNOLDS COMPANY, INC.

NEWARK, NEW JERSEY 07105
NEW ORLEANS, LA 70117
SAN FRANCISCO, CALIF 94104

LLONS

ACCEPTED

SP-1000

9682-1

CONTROL SNAILS
THE EASY WAY



CAUTION
KEEP OUT OF REACH OF CHILDREN

1/2 FLUID OUNCE

SHAKE WELL BEFORE USING

- HARMLESS TO HEALTHY FISH
- ADD ONLY ONE (1) DROP PER GALLON OF WATER
- SNAILS WILL BEGIN DYING IN 2 TO 3 HOURS... REMOVE BY SIFONING AND REPLACE WITH FRESH WATER. REPEAT IN THREE (3) DAYS IF NECESSARY.

ACTIVE INGREDIENTS: Cupric Ferricant-
late Complex (equivalent to 3.4% elemental
copper) 0.7%, Magnesium Sulfate 0.1%.

INACTIVE INGREDIENTS:
Water, Glycerin 04.2%

USA Reg. No. 58221
LOT NUMBER 68-021

ARSAN RESEARCH
WESTLAND, MICHIGAN 48185