

CAUTION

CONTAINS

BIS (TRIBUTYL TIN) OXIDE
AND CUPROUS OXIDE

DEVVOE®

MARINE

PAINTS & COATINGS - WORLD-WIDE

**DEVVAN MX075
BLACK ANTI-FOULING PAINT BASE
M^o 3748**

WARNING

KEEP OUT OF REACH OF CHILDREN

**VAPOR HARMFUL — COMBUSTIBLE
HARMFUL IF SWALLOWED**

Read carefully cautions on left panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY

4 U. S. GALLONS

IMPORTANT

The contents of this container are part of a two component DEVVAN[®] Epoxy system and must be mixed with Devvan[®] MD 4252 before application.

Directions for Use

Before treating surfaces, clean and remove all dirt, grease, oil, etc. from the surface. Remove all loose material and sandblast or sandpaper the surface. Add a thin coating of Devvan[®] MD 4252 to the surface. Allow to dry for 24 hours. Apply the DevVAN[®] MX075 Black Anti-Fouling Paint Base to the surface. Apply the DevVAN[®] MX075 Black Anti-Fouling Paint Base to the surface. Apply the DevVAN[®] MX075 Black Anti-Fouling Paint Base to the surface.

DEVVOE & RAYNOLDS
COMPANY, INC
NEWARK, NEW JERSEY 07102
NEW ORLEANS, LA 70112
SAN FRANCISCO, CALIF. 94104

USE WITH ADEQUATE
VENTILATION