

DEVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

DEVTRAN[®] 216 PERMANENT RED ANTI-FOULING PAINT

MD-3873

WARNING!

KEEP OUT OF REACH OF CHILDREN

VAPOR HARMFUL COMBUSTIBLE

HARMFUL OR FATAL IF SWALLOWED

FOR USE BY PROFESSIONAL APPLICATORS ONLY

Read Carefully WARNING On Left Panel

5 U.S. GALLONS

E.P.A. REG. NO. 246115

BATCH NO

ACTIVE INGREDIENT
Cuprous Oxide 34.50
INERT INGREDIENT 65.50

Net Weight 45.00
Metric 16.33

WARNING!

CONTAINS XYLOL, BUTYL
ALCOHOL AND
CUPROUS OXIDE

DO NOT USE, POUR, SPILL OR
STORE NEAR HEAT OR OPEN
FLAME

Avoid breathing of vapor or spray
mist.

Avoid contact with skin.

Close container after using.

Do not reuse empty container.

Destroy it by perforating or crush-
ing. Bury or discard in a safe place.

Do not contaminate water by
cleaning of equipment or disposal
of wastes.

FIRST AID: If swallowed, do NOT
induce vomiting. CALL A PHYSI-
CIAN.

USE WITH
ADEQUATE VENTILATION

DIRECTION FOR USE

Be sure that all surfaces are clean,
free of rust, grease, oil, grease or
oil. Remove all loose paint with
wire brush or scraper. Mix thor-
oughly, both by stirring and then
pouring into one clean container
to another several times. Stir from
time to time during application.

Apply one or two coats, using an
strip pattern by brush or roller, for
spraying, if necessary, with
No. 2 solvent. Mix of No. 2. Do not
add any solvents to this paint.
Allow four hours between coats.

Anti-fouling paint must be applied
over suitable barrier coats, and
should not be applied directly to
metal. It should not be applied to
painted surfaces. Use the proper
method of application.

DEVOE & RAYNOLDS
COMPANY, INC.

NEW ORLEANS, LOUISIANA
NEW ORLEANS, LOUISIANA
NEW ORLEANS, LOUISIANA