

CAUTION

CONTAINS

**BIS (TRIBUTYL TIN) OXIDE
AND CUPROUS OXIDE**

DO NOT USE POLAR SPILL OR STORE NEAR HEAT OR OPEN FLAME.

Avoid breathing of vapor or spray mist.

May be absorbed through skin. Causes skin irritation.

Avoid contact with skin, eyes or clothing.

Avoid storage near feed and food products.

Close container after using. Do not reuse empty container. Destroy it by puncturing or crushing and bury or discard in a safe place.

Do not contaminate water by cleaning of equipment or disposal of waste.

FIRST AID: If swallowed, induce vomiting. CALL A PHYSICIAN.

In case of skin contact remove contaminated clothing and wash skin with soap and water. For eyes, flush with plenty of water and get medical attention. Wash clothing before reuse.

**USE WITH ADEQUATE
VENTILATION**

DEVOE

MARINE

PAINTS & COATINGS · WORLD-WIDE

FORMULA 218

DEVTRAN PERMANENT RED ANTI-FOULING PAINT

MD-3888

WARNING!

**KEEP OUT OF REACH OF CHILDREN
VAPOR HARMFUL · COMBUSTIBLE
HARMFUL IF SWALLOWED**

Read carefully caution on left panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY

5 U. S. GALLONS

E.P.A. REG. NO. 9461-39

DIRECTION FOR USE

Be sure that all surfaces to be painted are free of moisture, scale, and old oil. Remove old paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from the can into another to another container. Allow five to ten minutes to settle.

Apply with brush, roller, or spray gun. Apply with brush or roller. Spray with DeVco No. 2 Sprayer MD-3888. Do not add more solvent to the paint. Allow four hours between coats.

Anti-fouling paint must be applied evenly and thoroughly. It should not be reapplied until the water is clear. Do not use on painted surfaces. Do not use on painted surfaces.

**DEVOE & RAYNOLDS
COMPANY, INC.**

NEWARK, NEW JERSEY 07102
NEW BRUNSWICK, NEW JERSEY 08901
NEW YORK, NEW YORK 10014

ACTIVE INGREDIENT		
Cuprous Oxide	67.25	
Bis-Tributyltin Oxide	2.00	
Inert Ingredients	67.25	
	100.00	
EPA REG. NO. 268-50001		
EPA REG. NO. 268-50001		
EPA REG. NO. 268-50001		