

CAUTION
CONTAINS
CUPROUS OXIDE,
BIS (TRIBUTYL TIN) OXIDE,
CHLOROPHENOLS AND
PETROLEUM DISTILLATE

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.

Avoid breathing of vapor or spray mist.

May be absorbed through skin. Causes skin irritation.

Avoid contact with skin, eyes or clothing.

Avoid storage near feed and food products.

Close container after using. Do not reuse empty container; destroy it by perforating or crushing and bury or discard in a safe place.

Do not contaminate water by cleaning of equipment or disposal of wastes.

FIRST AID: If swallowed, do not induce vomiting. CALL A PHYSICIAN.

In case of skin contact remove contaminated clothing and wash skin with soap and water; for eyes, flush with plenty of water and get medical attention. Wash clothing before reuse.

USE WITH ADEQUATE VENTILATION

DEVVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

ACCEPTED

NOV 19 1975

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 9461-89

SUPER TROPICAL ANTI-FOULING SHIP BOTTOM PAINT MD-3835

CAUTION
KEEP OUT OF REACH OF CHILDREN
VAPOR HARMFUL — COMBUSTIBLE
HARMFUL IF SWALLOWED

Read carefully precautions on left panel.

E.P.A. REG. NO. 9461-89

**5 U. S. GALLONS
(18.925 LITERS)**

ACTIVE INGREDIENTS

Cuprous Oxide	20.90%*
Copper Powder	2.58%*
Bis (Tributyltin) Oxide	1.76%*
Pentachlorophenol	2.00%
Related chlorophenols	0.23%
INERT INGREDIENTS	72.53%
	<hr/>
	100.00%

*Equivalent to 21.14% Metallic Copper and 0.70% Metallic Tin.

BATCH NO.

DIRECTIONS FOR USE ON STEEL HULLS

Be sure that all surfaces are clean, free of moisture, scale, grease or oil. Remove all loose paint with wire brush or scraper. Mix thoroughly, both by stirring and then pouring from one clean container to another several times. Stir from time to time during application. Apply one or two coats "as is" on ship bottoms by brush or roller. For spraying, thin if necessary with THINNER MD-542. Do not add oil or varnishes to this paint. Allow four hours between coats.

Super Tropical Antifouling Ship Bottom Paint MD-3835 must be applied over suitable barrier coats; do not apply directly to metal. For recommended primers and application information refer to Product Data Sheet on various Devvoe Anti-Corrosive Systems. Launching may be accomplished as soon as one hour after the final application of the antifouling coat.

FOR INDUSTRIAL USE ONLY IN COMMERCIAL AND NAVAL SHIPYARDS

MAF 3835/751 10/30/75

A Product of

DEVVOE & RAYNOLDS COMPANY, INC.

NEW YORK, N.Y. 10004
NEW ORLEANS, LA. 70117

EMERYVILLE, CALIF., 94608