

CAUTION

CONTAINS

**BIS (TRIBUTYL TIN) OXIDE
AND CUPROUS OXIDE**

DO NOT USE, POUR, SPILL OR
STORE NEAR HEAT OR OPEN
FLAME

Avoid breathing of vapor or spray
mist.

May be absorbed through skin.
Causes skin irritation.

Avoid contact with skin, eyes or
clothing.

Avoid storage near feed and food
products.

Close container after using. Do not
reuse empty container; destroy it
by perforating or crushing and
bury or discard in a safe place.

Do not contaminate water by clean-
ing of equipment or disposal of
waste.

FIRST AID: If swallowed, induce
vomiting. CALL A PHYSICIAN.

In case of skin contact remove con-
taminated clothing and wash skin
with soap and water; for eyes,
flush with plenty of water and get
medical attention. Wash clothing
before reuse.

USE WITH ADEQUATE

VENTILATION

DEVVOE

MARINE

PAINTS & COATINGS • WORLD-WIDE

**ANTI-FOULING PAINT
MD-3696**

WARNING

**KEEP OUT OF REACH OF CHILDREN
VAPOR HARMFUL—COMBUSTIBLE
HARMFUL IF SWALLOWED**

Read carefully caution on left panel
FOR USE BY PROFESSIONAL APPLICATORS ONLY

EPA REG. NO. 68132

ACTIVE INGREDIENTS

Cuprous Oxide	22.10
Triphenyltin Oxide	2.74
Bis (tributyltin) Oxide	1.46
VERTICAL PAINTS	73.37

100.00
EPA REG. NO. 68132
EPA REG. NO. 68132

Directions for Use

Be sure that all surfaces are clean,
free of moisture, scale, grease or
oil. Remove all loose paint with
wire brush or scraper. Mix thor-
oughly, both by stirring and then
pouring from one container
to another several times, just prior
to time of application.

Apply with a two coat system over
ship bottom, piers, etc. For
spray application, use a spray gun
MD-542 or other type spray gun
various sizes of nozzle. A nozzle
having a 1/2 inch orifice.

Anti-fouling paint should be applied
over a white or light color paint, and
should not be applied directly to
metal. Do not mix with any other
paints or solvents. The paint
should be applied in a thickness
from 24 to 36 mils, depending on
type.

**DEVVOE & RAYNOLDS
COMPANY, INC.**

NEWARK, NEW JERSEY 07105
NEW ORLEANS, LA 70117
SAN FRANCISCO, CALIF. 94104

5 U. S. GALLONS