

ALGEX 30

Water Treatment Microbiocide Concentrate for industrial recirculating cooling towers.

Active Ingredients:
 1 Hydroxyethyl-1-Benzyl-2-Alkyl (as in fatty acids derived from coconut oil)

GENERAL CLASSIFICATION

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For best results, slug feed. To optimize your use of ALGEX 30, follow this procedure:

1. Initially use 20 fluid ounces per 1000 gallons of water to be treated (25 ppm active quaternary).

Should the above dosage not give satisfactory results, use 32 fluid ounces per 1000 gallons of water (50 ppm).

Repeat every seven days or as needed.

2. When the above treatment level is successful, use 12 to 16 fluid ounces per 1000 gallons of water weekly as needed.

Should slime develop again, go back to initial dosage.

Dilute the appropriate amount of ALGEX 30 in 1 or 2 gallons of water, then add to the sump of the tower.

Should tower be heavily fouled, a pre-cleaning is required.

NET CONTENTS _____

LAB CONTROL NO. _____
 Manufactured by

CHARDON

Chardon Enterprises, Inc.

539 Stimmet Road, Box 1004, Columbus, Ohio 43216

43216

70

AIR 18 1981

Under the Federal Insecticide, Fungicide, and Rodenticide Act, amended for the registration of EPA Reg. No. 9000-11

AND
 R
 Do not
 Hazard
 Personal
 Equiv
 of dis
 place
 e res
 at dis
 edures