


Reg # 9630-11

PM-22

171



711

CONTROL NET TARE GROSS

4/22/92

P.O.#



# M-GARD<sup>TM</sup> W512 WOOD PRESERVATIVE WATER REPELLANT

## PRECAUTIONARY STATEMENTS WARNING

**HAZARDS TO HUMANS AND DOMESTIC ANIMALS**  
Causes substantial but temporary eye, nasal and skin irritation. Harmful if swallowed or absorbed through skin. Do not get in eyes, skin, or clothing. Wear goggles, face shield, or safety glasses. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Prolonged or repeated skin contact may cause allergic reactions in some individuals.

### ENVIRONMENTAL HAZARDS

Do not apply directly to water, to areas where surface water is present, or to intertidal areas below the mean high water mark.

### PHYSICAL OR CHEMICAL HAZARDS

Apply this product only as specified on the label. Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation. Close container after each use.

### STORAGE AND DISPOSAL PROHIBITIONS

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

### PESTICIDE DISPOSAL

Pesticide; spray mixture or rinse that cannot be used or chemically reprocessed should be disposed of according to procedures approved by federal, state or local disposal authorities.

### CONTAINER DISPOSAL

Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

### GENERAL

Consult federal, state or local disposal authorities for approved alternative procedures.

**HEALTH**

1

**FLAMMABILITY**

2

**REACTIVITY**

0

**PERSONAL PROTECTION**

B

ACTIVE INGREDIENT:  
Copper Naphthenate 58.00%  
(Copper, as metal, 6%)  
INERT INGREDIENTS 42.00%  
TOTAL 100.00%  
PRODUCT WT/GAL = 8.3 LBS.

## WARNING

CONTAINS PETROLEUM DISTILLATES  
HARMFUL IF SWALLOWED  
See other precautionary statements on side panel.

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT  
IN A MANNER INCONSISTENT WITH ITS LABELING.

EPA Reg. No. 9630-11  
EPA Est. No. 9630-PA-01

## KEEP OUT OF REACH OF CHILDREN WARNING

### STATEMENT OF PRACTICAL TREATMENT

**IF IN EYES:** Hold eyes open and flush with steady gentle stream of water for 15 minutes.  
**IF SWALLOWED:** Drink promptly a large quantity of milk, egg whites, gelatin mixture, or, if these are not available, large quantities of water. Avoid alcohol. Do not induce vomiting as it may cause respiration pneumonia.  
**IF ON SKIN:** Wash with plenty of soap and water. GET MEDICAL ATTENTION.

## DIRECTIONS FOR USE

For the control of fungal rot and decay in wood products, the wood should be sprayed, soaked or dipped, saturating the wood surface.

M-GARD W512 is an emulsifiable concentrate of copper naphthenate suitable for dilution and subsequent application to wood by brush, dip, spray or pressure impregnation including landscape logs and structural timbers, planking, siding, fences, greenhouse wood and stakes, millwork, plywood, shingles, structural logs, wood block flooring, non-apparel canvas (e.g. tents, tarpaulin, sails), wide timber, baskets, and lumber for ammunition boxes. Treated wood can be used as a staking material for various food plants with no additional precautions. M-GARD W512 will significantly reduce the deterioration of wood or canvas by dry rot, wet rot, fungal rot, and mildew growth. Wood products are colored by M-GARD W512 but oil-borne or water-borne coatings can be applied to treated wood which has dried thoroughly or has been sealed with shellac.

### APPLICATION

**PRESSURE TREATMENT:** For pressure treatment, dilute the M-GARD W512 with 19 volumes of water. Recirculation of the treating solution should be maintained. Maximum preservation is obtained by full cell pressure treatment, as conducted to obtain an average copper retention of 0.07 pct.

**DIP, BRUSH, SPRAY:** When treating by DIP, reduce the M-GARD W512 with 2 volumes of water. Maintain good agitation in the dip emulsion. Completely immerse for 5 minutes, consuming one pint of emulsion per cu.ft. of wood. The dip emulsion containing two volumes of water may also be used for maximum protection by brush, spray treatment. **FOR BRUSH, SPRAY:** Spray or brush until surface is completely wet with repeat applications after the emulsion has been absorbed by the wood to provide additional penetration.

**CANVAS, FOUNDATION TIMBERS:** For canvas dip, soak, or spray until fabric is completely wet. For foundation timbers and other wood products involving ground contact, wood should be free of bark and soaked until sapwood is completely penetrated. Dilution ratios are fixed to meet Federal Specifications. If no Federal Specification is involved, the recommended dilution level is 1-2% copper.

ALWAYS ADD M-GARD TO WATER.

UNFAILING INTEGRITY · QUALITY · DELIVERY



# Mooney Chemicals, Inc.

TWO MILE RUN RD., FRANKLIN, VENANGO COUNTY, PA. 16323 - 814/432-2125