

**KEEP OUT OF REACH OF CHILDREN**  
**WARNING**

**HARMFUL IF SWALLOWED**

Statement of practical treatment

If swallowed: do not induce vomiting. Get medical help.

If inhaled: remove to fresh air.

If on skin: wash with soap and water.

If eyes: flush immediately with water.

**PRECAUTIONARY STATEMENTS**  
**WARNING**

**Hazards to Humans and Domestic Animals**

Avoid contact with skin, eyes or clothing. In case of contact, immediately flush eyes or skin with plenty of water. Use only with adequate ventilation. Avoid breathing of vapor or spray mist.

**Environmental Hazard**

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

**Physical Chemical Hazard**

Combustible: do not use or store near heat or open flame.

**ACTIVE INGREDIENT:**

Copper Naphthenate 80%  
(8% metallic copper equivalent)

**INERT INGREDIENTS:** 20%

**TOTAL** 100%

EPA Reg. No. 9630-12

EPA Est. No. 9630-PA-01

**STORAGE AND DISPOSAL**

**Prohibitions**

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

**Storage**

Store between 0°F and 140°F. Store in original container only. Keep container closed when not in use.

**Pesticide Disposal**

Pesticide, spray mixture, rinsate or wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

**Container Disposal**

- (a) Reseal container and offer for reconditioning or
- (b) Triple rinse (or equivalent) and offer for recycling, reconditioning or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**General**

Consult federal, state or local disposal authorities for approved alternative procedures.

**DIRECTIONS FOR USE**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**Wood Preservation**

FOR THE CONTROL OF FUNGAL ROT AND DECAY IN WOOD PRODUCTS, the wood should be dipped or soaked in a 25% solution of M-GARD™S520 in hydrocarbon solvent for from three minutes to 48

M-GARD™S520 may be used.

ALTERNATELY, IF THE PRESERVATIVE IS TO BE APPLIED TO WOOD PRODUCTS BY PRESSURE TREATMENT PROCESSES, the 12%