

M-GARD S540

WOOD PRESERVATIVE

ACCEPTED

JAN 9 1988

PRODUCT CODE

LOT NUMBER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS WARNING

Harmful if swallowed. Do not exceed specified application rate. Use only the application method specified for a particular use.

Do not get on skin, or on clothing. Prolonged or repeated skin contact may cause allergic reaction in some individuals. Wear long sleeved shirt, long pants, and hand protection such as rubber, or chemical resistant gloves.

Do not get in eyes. Wear protection such as goggles, face shield or safety glasses.

Do not breathe vapors or mist during brush, roll, spray and dip applications. Wear a NIOSH/MHSA-approved mist/vapor respirator when spraying for continued or prolonged use of this product or for frequent use of this product.

In case of medical questions, emergencies, or accidents involving this product, call 1-800-390-4444.

Application of this product may produce a strong, lingering, unpleasant odor.

ENVIRONMENTAL HAZARDS

EFFLUENT DISCHARGE STATEMENT

This product is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS

Apply this product only as specified on the label. Do not use, pour, spill or store near heat or open flame. Use only with adequate ventilation. Close container after use.

STORAGE AND DISPOSAL

STORAGE: Store at temperatures between 0 F and 100F. If product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbant, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in original container only. Keep container closed when not in use.

CONTAINER DISPOSAL: Triple rinse (or equivalent), then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by procedures approved by state and local authorities.

PESTICIDE DISPOSAL: Pesticide, spray mixture or rinsate that cannot be used or chemically reprocessed should be disposed of according to procedures approved by federal, state or local authorities.

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal.

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. 9630-15

INGREDIENTS:

ACTIVE INGREDIENT:
Copper Naphthenate.....19.25%
(Copper, as metal, 2%)

INERT INGREDIENTS.....80.75%
TOTAL.....100.0%

CONTAINS PETROLEUM DISTILLATES

PRODUCT WT/GAL.= 6.8 LBS.

KEEP OUT OF REACH OF CHILDREN

WARNING

STATEMENT OF PRACTICAL TREATMENT

IF IN EYES: Hold eyes open and flush with steady gentle stream of water for 15 minutes.

IF SWALLOWED: Drink promptly a large quantity of milk, egg whites, gelatin mixture, or, if these are not available, large quantities of water. Avoid alcohol. Do not induce vomiting as it may cause respiratory pneumonia. GET MEDICAL ATTENTION.

IF ON SKIN: Wash with plenty of soap and water.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT
IN A MANNER INCONSISTENT WITH ITS LABELING
FOR EXTERIOR USE ONLY

WOOD PRESERVATIVE: For the control of fungal rot and decay, mold and mildew, moss, termites, (including Formosan termites) and other wood destroying insects in wood products. **APPLICATIONS FOR M-GARD S540 WOOD PRESERVATIVE FOR WOOD SURFACES IN CONTACT WITH SOIL, CONCRETE OR WATER INCLUDE FOUNDATION SILLS, DOCKS, BOATS, AND FENCE POSTS.** M-Gard S540 is only intended for use on exterior wood. Do not use for wood intended for: direct contact with food or food crops; prolonged exposure to livestock such as pens, stalls, and feeding troughs; and containers designated for the storage of potable water. Wood exposed in or over aquatic environments such as boats, docks, and bridge timbers shall be treated prior to installation in or over the aquatic environment to assure the liquid preservative is not allowed to enter the water. M-Gard S540 Wood Preservative provides protection against moisture, rot and mildew on any natural wood surface. This copper naphthenate wood preservative and insecticide will preserve and protect wood surfaces that will be in contact with soil, water, or concrete.

The copper fungicide gives a green cast to M-GARD S540 Wood Preservative. This product is not intended for use as a stain. The green color will fade within a few months when exposed to sunlight. Oil or alkyd stains or paints can be applied over M-GARD S540 Wood Preservative after overnight dry but the green may bleed through lighter colors. Do not over-coat M-GARD S540 Wood Preservative with latex paint or clear finishes until thoroughly cured (6-12 months).

WOOD PREPARATION: Wood should be clean, dry, well seasoned, and free of bark. Do not apply M-GARD S540 over painted or varnished surfaces. Do not apply over bark. Application of M-GARD S540 to wood which has been previously treated with a coating such as paint or varnish will provide limited or penetration and protection.

DIP, BRUSH AND ROLL APPLICATIONS: For dipping applications, soak the wood products for a minimum of one minute. The rate of coverage for brushing, rolling and dipping is typically one gallon per 100-300 sq. ft. Do not thin- Materials supplied at proper application consistency. Use one coat on materials to be finished with paint or stain. If no finish is to be used, apply two liberal coats within one hour. Thoroughly cover ends. The more preservative absorbed by the wood, the longer and more effective the protection period. Clean painting equipment with mineral spirits for quick clean up.

SPRAY APPLICATIONS: The rate of coverage for spraying is typically one gallon per 100-300 sq. ft. Do not thin- Materials supplied at proper application consistency. Use one coat on materials to be finished with paint or stain. If no finish is to be used, apply two liberal coats within one hour. Thoroughly cover ends. The more preservative absorbed by the wood, the longer and more effective the protection period. Clean painting equipment with mineral spirits for quick clean up.

EPA Reg. No. 9630-15
EPA Est. No. 9630-PA-1

For general information, questions or comments about this product,
call OMG AMERICAS, INC. at 1-814-432-2125.



UNFAILING INTEGRITY - QUALITY - DELIVERY

OMG AMERICAS, INC.
OMG Franklin
OMG Apex

TWO MILE RUN RD.
VENAGO COUNTY, PA 16323 * 814. 2125

pm 24
9630-15
1-814-432-2125