CONTROL

*O* 

NET

**TARE** 

**GROSS** 

## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

## CAUTION

#### FIRST AID PROCEDURE

Harmful if swallowed or absorbed through skin. Avoid contact with eyes, on skin or on clothing. Wash thoroughly after handling.

IF SWALLOWED, Do not induce vomiting, CALL PHYSICIAN IMMEDIATELY. — IF ABSORBED THROUGH SKIN, Wash thoroughly with soap and water. — IF IN EYES, Flush with plenty of water and get immediate medical attention. — CONTAMINATED CLOTHING should be removed and washed thoroughly before reusing.

## **ENVIRONMENTAL HAZARDS**

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on the label.

#### PHYSICAL OR CHEMICAL HAZARDS

Use only with adequate ventilation. Close container after each use.

## **DIRECTIONS FOR USE**

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

## STORAGE AND DISPOSAL

Product will freeze. Store at temperatures between 40°F, and 100°F. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread Absorbant, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Keep container closed when not in use.

Do not use empty container. Wrap container and put into trash collection.

## **FUNGICIDAL ACTIVITY**

Protects and preserves wood against mold, mildew, rot, wood destroying fungi mildew stain and attack by termites.

### **NOTES TO USER**

Do not apply over painted or varnished surfaces. Do not apply over bark.

Do not use on wood intended for food, feed, potable water, livestock or dairy animals contact surfaces.

May injure living plants during application. Cover plants to protect against direct contact.

# (m) GARD W566

## **WOOD PRESERVATIVE**

ACTIVE INGREDIENT:	
Zinc naphthenate*	15.7%
INERT INGREDIENTS	84.3%
TOTAL	100.0%
*(Equivalent to 2% Zinc Metal)	

PRODUCT WEIGHT PER GALLON - 8.3 LBS.


## KEEP OUT OF REACH OF CHILDREN

## CAUTION

See other precautionary statements on side panel.

MOONEY CHEMICALS, INC. 2301 Scranton Road Cleveland, Ohio 44113

> EPA Reg. No. 9630-18 EPA Est. No. 9630-PA-01



## PM 21 APPLICATION SITE 1001

Can be used to present that the same exterior wood. Interior use is only needed when wood is subject to frequent of prolanged vetting (e.g. condensation or rain seepage.) Can be used for above ground, ground contact and below ground uses. Below ground or ground contact use requires a minimum 5 minute dip. For even-further protection, dip for one how. Wood to the freated should be dry and well séasoned. Fence posts must have bark removed. For fence posts, finished timbers to be buried in soil, immersion for 12-48 hours provides long term protection (pine species may be adequately penetrated in 6-8 hours). Cut timbers should be immersed 15-30 minutes per inch of thickness, except in case of pine species which absorbs the preservative at a faster rate. For above ground use, apply two brush coats or dip for 3 minutes per inch of thickness. All wood should be treated after all cuts are made and before use in the structure.

#### PROTECT PRODUCT FROM FREEZING

## **FABRIC AND CORDAGE PROTECTION**

Can be used to protect and preserve fabric against mildew, mold and fabric destroying and staining fungus, including rope, fish net, twine, canvas, burlap and other fabrics. Materials should be thoroughly saturated until wet and air dried before use. Material can be either sprayed or dipped for complete saturation. Treats approximately 75 square feet of fabric per gallon. Do not use on fabric intended for food or feed contact surfaces or clothing. Not for use on fabric or cordage in ground contact situations.

#### WOOD PRESERVATIVE USES

Protects the following types of wood: shingles, millwork, windows, outdoor furniture, docks, piers, posts, pilings, block flooring, staking material, decks, spars, house siding. Protects wood in all the above applications including nursery lumber, slats, and beenive crates.

## PHYSICAL PROTECTION

inhibits warping, shrinking, swelling, checking, cracking, water marking of the wood. Can be painted after drying for 24 hours. For wood containing resins and other materials weathering will enhance paint adhesion. This colorless product offers a penetrating fungicide which will not bloom.

#### COVERAGE

100-300 square feet - depending on porosity of wood and method of application.