



9630-01 10F1
\$550 ACCEPTED
 FEB 28 1986

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under:
 EPA Reg. No. 9630-01

KEEP OUT OF REACH OF CHILDREN
CAUTION
HARMFUL IF SWALLOWED
 Statement of practical treatment
 If swallowed: do not induce vomiting. Get medical help.
 If inhaled: remove to fresh air.
 If on skin: wash with soap and water.
 If in eyes: flush immediately with water.

ACTIVE INGREDIENT:
 Zinc naphthenate 63%
 (Zinc, as metal, 8%)
INERT INGREDIENTS 37%
TOTAL 100%

EPA Reg. No. 9630-ER
 EPA Est. No. 9630-PA-01

Weight Per Gallon - 8.3 lbs.

PRECAUTIONARY STATEMENTS
CAUTION
Hazard to Humans and Domestic Animals
 Avoid contact with skin, eyes or clothing. In case of contact, immediately flush eyes or skin with plenty of water. Use only with adequate ventilation. Avoid breathing of vapor or spray mist.
Environmental Hazard
 This product is toxic to fish. Do not add directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.
Physical Chemical Hazard
 Combustible: do not use or store near heat or open flame.

STORAGE AND DISPOSAL
Prohibitions
 Do not contaminate water, food or feed by storage disposal. Open dumping is prohibited.
Storage
 Store between 10°F and 100°F. Store in original containers only. Keep containers closed when not in use.
Pesticide Disposal
 Pesticide Spray mixture, rinsate or wastes resulting from the use of this product should be processed according to procedures approved by federal, state or local authorities.
Container Disposal
 Triple rinse (or equivalent) and offer for recycling, reconditioning or puncture and dispose of in a sanitary landfill or by other procedures approved by state or local authorities.

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

M-GARD S550 is a concentrate of zinc naphthenate suitable for dilution with various solvents and subsequent application on wood as a preservative. Wood to be treated is intended for exterior use - logs, lumber, timber, fences, millwork, plywood, poles, siding, staking material & nursery lumber.

Application can be by brush, dip or pressure impregnation. Dip & pressure treatment are recommended for ground contact use. M-GARD S550 will protect wood against attack by dry rot, wet rot, fungal rot, mildew & termites. Paint can be applied over treated surfaces.

M-GARD S550 can also protect canvas and cordage (i.e. fish netting) from fungal rot & mildew.

DIRECTIONS FOR USE - WOOD PRESERVATION

WOOD - For dip treatment reduce M-GARD S550 with between 1 2/3-3 parts by weight with solvent (i.e. mineral spirits, mineral oil, fuel oil) depending on severity of conditions. For above ground use, immerse wood 1-3 minutes per inch of thickness. For below ground, 5 minutes per inch of thickness.

For pressure treatment by full cell, dilute M-GARD S550 with 39 volumes of a recommended solvent. Obtain an average zinc retention of 0.09 pcf.

For brush treatment, 2 liberal coats is recommended for above ground use if no topcoat is to be applied. One coat is sufficient if treatment is to be topcoated.

CANVAS & CORDAGE - Materials should be thoroughly saturated by dip application & air dried before use.

NOTE TO USER - Do not use on wood, canvas or cordage intended for food, feed, potable water, livestock or dairy animal contact surfaces. Do not use on fabric intended for clothing or ground contact applications.

UNFAILING INTEGRITY - QUALITY - DELIVERY

Mooney