

PM 21

9639-2

1 of 2

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

SEP 25 1989

053537	300
2	17

John M. DeLong
 Willard Products
 70 Chemical Way
 P.O. Box 249
 Redwood City, CA 94064

Dear Mr. DeLong

Subject: Amended Labeling
 Copper Green
 EPA Registration No. 9639-2
 Your Submission Dated September 29, 1989

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. A stamped copy is enclosed for your records.

Sincerely yours,

Susan Lewis
 Product Manager (21)
 Fungicide-Herbicide Branch
 Registration Division (H7505C)

BEST AVAILABLE COPY

55169:I:A-4:Stone:R-1:KENCO:2/13/90:3/16/90:dg:vo:sw:jh:dg

CONCURRENCES

SYMBOL							
SURNAME							
DATE							

292

BEST AVAILABLE COPY

M-GARD S540-0

**ACCEPTED
with COMMENTS
in EPA Letter Dated:**

SEP 12 1989

RTU SOLUTION

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

9630-15

**COPPER FUNGICIDE - INSECTICIDE
FOR WOOD**

**PREVENTS WOOD DECAY - TERMITES, M
INCLUDING POLES AND POLETOPS, BORE HO
POSTS, BEAMS, LUMBER, BRIDGE TIMBERS AND**

DIRECTIONS FOR USE
It is a violation of Federal law to use this product in
a manner inconsistent with its labeling.

APPLICATION SITE

M-GARD S540-O is only intended for use on exterior wood.
Do not apply to food or feed contact surfaces. Do not
contaminate drinking water with treated articles.
M-GARD S540-O Wood Preservative provides protection
against moisture, rot and mildew on any natural wood
surface. This copper naphthenate wood preservative and
insecticide will preserve, protect and seal wood
surfaces that will be in contact with soil, water or
concrete.

The copper fungicide gives a green cast to M-GARD S540-O
Wood Preservative. This product is not intended for use
as a stain. The green color will fade within a few months
when exposed to sunlight. Oil or alkylid esters or paints
can be applied over M-GARD S540-O Preservative after
overnight dry but the green may bleed through lighter
colors. Do not over coat M-GARD S540-O Wood Preservative
with latex paint or clear finishes until thoroughly cured
(6 to 12 months).

PREPARATION

Wood should be clean, dry, and seasoned.

APPLICATION

M-GARD S540-O Wood Preservative should be
applied liberally by brush, roller, spray, total immersion,
or internal injection under pressure for the prevention
and control of fungal decay organisms.

Dipping-Wood should be dipped for 3 to 30 minutes per
inch of thickness. Fence posts, piles, poles, foundation
timbers and heavy wooden members should be free of bark,
dry, and well seasoned and immersed in the product for
a period of 12 to 48 hours to be an effective wood
preserver.

Internal Treatment-To internally treat previously treated
utility poles or other foundation timbers apply M-GARD
S540-O solution to internal cavity of wood structure through
prepared openings using air or mechanical pressure pump.
Apply one gallon or to refusal.

Do not thin-material is supplied at proper application
consistency.

Use one coat on materials to be finished with paint or
stain. If no finish is to be used, apply two liberal coats
within the hour. Thoroughly cover ends. The more
preservative absorbed by the wood, the longer and more
effective the protection.

Clean painting equipment with mineral spirits for quick
clean up.

ACTIVE INGREDIENT:	
Copper Naphthenate	19.25%
(2% copper as metal)	
INERT INGREDIENTS:	80.75%
TOTAL	100.00%
Product Wt./Gal.	6.8 Lbs.

**KEEP OUT OF REACH OF CHILDREN
WARNING**

**HARMFUL IF SWALLOWED
COMBUSTIBLE
CONTAINS PETROLEUM DISTILLATES**

It is a violation of Federal law to use this
product in a manner inconsistent with its
labeling.

EPA Reg. No. 9630-15
EPA Est. No. 9630-PA-01