

DIRECTIONS

This product is a clean oil solution useful for the protection of wood against fungus growths which cause rot and stain, termites, Lyctus (powder-post) beetles and carpenter ants, and contains water repellents to aid in the control of shrinking, swelling, end checking, grain raising and warping.

WOOD PRESERVATION AND DIMENSIONAL CONTROL

For best results, this product should be applied so as to effect maximum penetration into the wood and heavy absorption especially at joints and wherever end grain exists. A 3-minute immersion period is recommended for millwork. For other open tank treatments, complete immersion of the wood in the Willard-Tox solution is generally recommended for five minutes per inch of thickness. For the control of dimensional changes, shrinkage and swelling, the treatment of the end grain is most important since the moisture pick-up there is a hundred to a thousand times greater than at the flat or edge grain surface for many species of wood.

Where open tank treating is impractical as in the case of an existing structure, two heavy brush applications of this product should be applied, cutting out and removing all unsound wood two feet beyond any visible evidence of decay. All wood should be normally dry, and the framing or cutting completed before application of this product.

Do not paint or varnish wood that has been treated with this product until the excess petroleum solvents have volatilized from the wood.

Estimated Coverage: 5 to 10 gallons per thousand board feet for open tank treatment; 50 square feet per quart for brush application.

NOTICE

Manufacturer and/or Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.

This product is effective for application to wood for the control of termites, powder-post (Lyctus) beetles and carpenter ants. In all of these cases, it will be effective only in the areas of the wood contacted by the solution. Therefore, thoroughness of treatment is essential to good control.

Continued, Opposite Side

Willard Penta-Tox

EPA EST NO. 9639-CA-1

EPA REG. NO. 9639-7

WATER REPELLENT

AND

PENTA PRESERVATIVE

CAUTION: COMBUSTIBLE MIXTURE

ASSAY

ACTIVE INGREDIENTS:

Pentachlorophenol*	4.3%
Other Chlorophenols	0.5%

INERT INGREDIENTS:

WR-340 Concentrate	10.5%
Mineral Spirits	84.5%
Inerts from Tech.	
Pentachlorophenol	0.2%
Total	100.0%

*5.2% Technical Pentachlorophenol as
as defined in Fed Spec TT-W-570

NET CONTENTS: 1 GALLON

INTERNAL ANTIDOTE: ...
EXTERNAL ANTIDOTE: ...
DANGER: ...

WARNING: KEEP OUT OF REACH OF CHILDREN

WARNING

Harmful or fatal if swallowed or absorbed through skin! Causes skin irritation! Do not breathe vapor or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling. Do not store or use near open flames.

Avoid contamination of feed and food stuffs.

Wear protective clothing and rubber gloves when handling the freshly treated lumber.

DIRECTIONS (Continued)

TERMITE CONTROL: For protection of new wood prior to installation, see instructions on wood preservation and dimensional control. For application to wood in place to protect against subterranean or drywood termite damage, apply the solution to run-off, allow to soak in, and make at least one more application. Care must be exercised that the solution does not contact asphaltic products (tar paper, composition shingles, or other such items) or that it is not applied in such a way that it will stain plaster or other surfaces. Treatment of the wood is supplemental to soil treating. Trenches around foundations should be 30 inches deep but not below the top of the footing if this is shallower. The rate of application should be 5 (five) gallons of a 5 per cent solution per 10 linear feet of trench up to 15 inches deep and 10 gallons per linear feet for deeper trenches. Grass trees, and shrubs within 3 feet of the trench should be removed or protected with tar paper.

POWDER-POST BEETLE CONTROL: Lumber, flooring or other items infested with powder-post beetles can be controlled by immersing the wood in this product for a minimum of 5 minutes per inch of thickness.

This product is not to be used for indoor purposes.

CARPENTER ANTS: This product applied to infested wood either by spraying or by injection into the cavities made by the ants, has proved useful for cleaning out ants living in the treated wood. Since poisoning of the colony at their source is the surest remedy, treatments of infested wood are usually supplemental.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

Apply this product only as specified on this label.

DO NOT REUSE CONTAINER

DESTROY WHEN EMPTY.

MANUFACTURED BY

WILLARD PRODUCTS

Redwood City, Calif. 94064