

ALGAECIDE - NF

COMPOSITION

	Percent by weight
Active Ingredient	10.0 percent
Poly (oxyethylene(dimethyliminio) ethylene (dimethyliminio) - ethylene dichloride).....	10.0 percent
Inert ingredient.....	90.0 percent
Weight per gallon.....	8.49 pounds
Weight of active ingredient per gallon.....	0.85 pound

APPLICATION

ALGAECIDE-NF is used to control algae, bacteria and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 6.13 to 15.32 fluid ounces of ALGAECIDE-NF per 1000 gallons of water to provide a concentration of 48 to 120 parts per million of ALGAECIDE-NF based on the total weight of water in the system is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.53 to 15.32 fluid ounces of ALGAECIDE-NF per 1000 gallons of water (12 to 120 parts per million of ALGAECIDE-NF) should be employed every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

CAUTION - KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. Avoid contact with skin and eyes. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds or public water. Do not contaminate water by cleaning of equipment or disposal of waste. Use only as directed on label. Do not reuse container. Destroy when empty.

EPA Reg. No. 9657-6

Manufactured By

SOLVENT MANUFACTURING CO., INC.

Manufacturing Chemists and Water Treatment Consultants
1517 OCAMA Blvd. -- Midwest City, Okla. 73110

Net Contents _____ Gals.

9657-6
July 30, 1973



ACCEPTED WITH COMMENTS