

**SER**

.....10%  
.....2.5%  
.....87.5%  
.....100%

get in eyes. In

batching tanks  
dough troughs,

**DIRECTIONS FOR REMOVING AND CONTROLLING THE GROWTH OF MOLD AND BACTERIAL SLIME ON PAINTED SURFACES, MASONRY, STEEL AND GALVANIZED METAL.**

1. Clean the molded or slimy surfaces thoroughly with a detergent solution containing 2 ounces of Blue Boy Cleaner per gallon of water to remove materials that prevent best action of RAMROD MOLD CHASER. Rinse thoroughly with clear tap water and allow surface to dry completely.
2. Using the measuring cup provided, add one fluid ounce of RAMROD MOLD CHASER to one gallon of tap water and mix well.
3. Apply diluted solution of RAMROD MOLD CHASER in sufficient quantity to thoroughly wet the surface and still not cause drippage of excess liquid. (DO NOT USE CONCENTRATED RAMROD MOLD CHASER, AS IT IS MUCH TOO STRONG!)
4. After twenty-four hours, clean the surfaces again with detergent solution and apply diluted Mold Chaser solution as before, allowing it to remain on the surfaces as a protective film.
5. Treatment may be repeated as needed on a regular maintenance schedule to control the growth of mold and slime.

**DIRECTIONS FOR SANITIZING FOOD PROCESSING EQUIPMENT**

1. Clean the equipment thoroughly using the proper detergent. DO NOT USE SOAP OR ANIONIC DETERGENTS.
2. Rinse thoroughly with clear tap water to remove soils and cleaning solution.
3. Using the measuring cup provided, add 1 fluid ounce of RAMROD MOLD CHASER to 4 gallons of tap water and mix well.
4. Sanitize cleaned, rinsed equipment thoroughly with the solution of RAMROD MOLD CHASER by scrubbing, spraying or immersing equipment. Rinsing is not required at this concentration.
5. DO NOT TOUCH SANITIZED EQUIPMENT OR OTHERWISE ALLOW IT TO BECOME CONTAMINATED.

**RINSE EMPTY CONTAINER THOROUGHLY WITH WATER AND DISCARD IT.**

Contents: 1 Gallon

PACKED BY:

EPA Reg. No. 9681-7

**RAMROD CHEMICALS**

**P. O. BOX 2640 • 6630 MAPLE AVE. • DALLAS, TEXAS 75221**