



# PABCO

## Decorator

**preserv-wood**

clear  
**1075**

**DANGER**

**FLAMMABLE**

**HARMFUL OR FATAL IF SWALLOWED**

**KEEP OUT OF REACH OF CHILDREN**

**SEE CAUTIONS ON BACK OF LABEL**

**ONE U.S. GALLON**

**PRESERV-WOOD**

**Active Ingredients**  
 Pentachlorophenols . . 4.4%  
 Other Chlorophenols . 0.6%  
 Petroleum Distillate . . 90.0%  
 Inert Ingredients . . . . . 5.0%  
**ANTIDOTE:** External: Wash with Rubbing Alcohol and follow with soap and water. Internal: Give a tablespoon of salt in a glass of warm water and repeat until vomit fluid is clear. Give milk or white of eggs beaten with water. Have patient lie down and keep warm. **CALL A PHYSICIAN.**



**U.S.D.A. REG. 999-3**

**ACCEPTED**  
 NOV 29 1968  
 UNDER THE  
 FUNGICIDE ACT  
 FOR F. NO. 1075  
 ED UNDER NO. 1075  
 NO ATTACHED COMMENTS

**WARNING! FLAMMABLE: HAZARDOUS LIQUID AND VAPOR.** May cause skin irritation. Keep away from heat, sparks, and open flame. Avoid breathing vapor or spray mist, and contact with skin. In case of contact, wash skin with soap and plenty of water; flush eyes repeatedly with water. Keep container closed when not in use. **USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

**DIRECTIONS**

A clear wood preservative containing pentachlorophenol for protection against termites, wood-boring insects and wood rotting fungi. Will not swell or distort wood and is clean to handle. Ideal for use on fence posts, poles, mud sills, and window and door sills. Non-staining and may be painted over without bleeding or discoloration.

For best results use dip method of application. Immerse wood for 5-10 minutes, allowing about five minutes for each inch of thickness.

Under extreme preservation conditions allow the wood to soak until it absorbs

about six pounds of solution per cubic foot. Different woods will absorb from 1/4-3/4 gallons per cubic foot. When dipping is not practical, apply generously with brush or spray.

Fence posts and poles, to be properly treated, should be dry, free of bark and well seasoned.

Temperature should be above 40° F. before applying.

Dries in approximately one hour. Spread rate approximately 100-400 square feet per gallon depending upon porosity of wood. No thinning is necessary. Clean equipment with paint thinner.

Net contents one U.S. Gallon or 3.785 Litres  
 Equal to 133 Imperial Fluid Ounces



**PABCO PAINT**

CORPORATION

EMERYVILLE CALIFORNIA 94608

MADE IN U.S.A.