

US ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (75-767) WASHINGTON, DC 20460	EPA REGISTRATION NO.	DATE OF ISSUANCE
	9800-25	OCT 13 1987
	TERM OF ISSUANCE	
NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)	NAME OF PESTICIDE PRODUCT	
	Fuelcide - H.D.	

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Stewart Hall Chemical
 222 Washington Street
 Mt. Vernon, NY 10553

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.


Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Add the phrase "EPA Registration No. 9800-25" to your label before you release the product for shipment.
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the 4-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(c). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.



John H. Lee
 Product Manager (31)
 Disinfectants Branch
 Registration Division (TC-767C)

Enclosures

ATTACHMENT IS APPLICABLE

BEST AVAILABLE COPY

SIGNATURE OF APPROVING OFFICIAL	DATE
---------------------------------	------

OCT 13 1987

Stewart Hall Chemical
222 Washington Street
Mt. Vernon, NY 10553


Attention: Ms. Linda S. Allen

Gentlemen:

Subject: Fuelcide-H.D.
EPA Registration No. 9800-25
Your Submission Dated August 11, 1987

We acknowledge your August 11, 1987 submission stating that the above-named product will be packaged in pints, quarts, and gallons in addition to the sizes previously listed. This information has been made a part of the product file.

Sincerely yours,


John H. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

BEST AVAILABLE COPY

16729:I:Lee:L-9:KENCO:9/10/87:9/21/87:lf:VO:EK:lf

CONCURRENCES							
SYMBOL							
SURNAME							
DATE							

OFFICIAL FILE COPY

BEST AVAILABLE COPY

FUELCIDE - H.D

INDUSTRIAL MICROBICIDE

ACTIVE INGREDIENTS:	
Methylene bis(thiocyanate)	2.5%
2-IThioocyanomethylthiolbenzothiazole	2.5%
INERT INGREDIENTS	95.0%

This product weighs 7.99 pounds per gallon.

**KEEP OUT OF REACH OF CHILDREN
DANGER**

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

DANGER: Corrosive, causes irreversible eye damage and causes skin damage. Harmful or fatal if swallowed or absorbed through the skin. This product is a potential skin sensitizer. Workmen handling this product or treated material should wear impervious gloves, goggles or face shield, and protective clothing. All protective clothing, work shoes or boots, and equipment must be left at the work site at the end of the day. Eating, drinking, or smoking during use of this product is prohibited.

FIRST AID: In case of skin contact, wash promptly and thoroughly with soap and water and finally with glycerin. If product gets in the eyes, flush immediately with copious amounts of clean cool water for 15 to 30 minutes. Get medical attention immediately. If product is swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water or wetlands. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not expose to extreme temperatures.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.
STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

DIRECTIONS FOR

It is a violation of Federal law to use this product in a **FUELCIDE - H.D.**

COOLING TOWERS: **FUELCIDE - H.D.** wood against soft or surface rot and internal or dry rot. It is applied to surfaces containing 2.0 to 2.8% **FUELCIDE - H.D.** surfaces. The amount applied should provide 2.4 to 3.2 lb of **FUELCIDE - H.D.** per 1000 ft² of wood surface. Soft or surface rot can also be controlled by **FUELCIDE - H.D.** to the recirculating well. The dosage should provide 5.0 lb of **FUELCIDE - H.D.** per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hr after treatment. Repeated every four months.

COOLING WATER: **FUELCIDE - H.D.** and fungi in industrial recirculating cooling water systems. The system should be cleaned thoroughly to remove old algal growth, microorganisms; then should then be drained, flushed, refilled with water, and treated with **FUELCIDE - H.D.** per 1000 gal of water. Dosage of 0.8 to 4.8 fl oz per 1000 gal should be made every 1 to 5 days depending on the severity of microbiological fouling.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of drilling fluids, **FUELCIDE - H.D.** should be added in concentrations of 0.2 to 1.0% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: **FUELCIDE - H.D.** control sulfate-reducing bacteria, slime-forming bacteria, micellar floods, water disposal systems, and other oil-field water treatment systems. **FUELCIDE - H.D.** per 1000 made continuously or intermittently by means of a metering pump after injection pumps and injection well headers. Continuous application, add 15.6 to 52.0 fl oz **FUELCIDE - H.D.** per 1000 continuously until desired degree of control is achieved. Then add **FUELCIDE - H.D.** per 1000 gal of water.

control. Intermittent or Slug Method: When system is not fouled, add 15.6 to 52.0 fl oz **FUELCIDE - H.D.** per 1000 and 1 to 4 times per week, or as needed to maintain control.

CRUDE AND REFINED OILS: **FUELCIDE - H.D.** preventive for the control of bacteria and fungi that cause the degradation of oil during storage. It should be added to the oil as it is being transferred to storage tank at the rate of 2.4 to 24.0 fl oz **FUELCIDE - H.D.** per 1000. Addition should be made batchwise where mixing occurs or transfer pump.

Manufactured by:
STEWART HALL CHEMICALS
222 WASHINGTON ST.
MT VERNON, NY 10553

EPA REG. NO. _____ EPA EST. NO. _____

NET CONTENTS _____