

FRONT PANEL

M u n i C h e m

SUPER WEED AND BRUSH CONTROL

ACTIVE INGREDIENT

Ammonium Sulfamate.....48.4%

INERT INGREDIENTS.....51.6%

Contains 5.32 lbs. of ammonium sulfamate
per gallon

CAUTION: KEEP OUT OF REACH OF CHILDREN

MAY CAUSE SKIN IRRITATION

In case of contact, wash off with plenty of water.

U.S.D.A. Registration No.

MuniChem Corporation

Sparks, Nevada New York, New York Atlanta, Georgia Milwaukee, Wisconsin

SIDE PANEL

ACCEPTED

Dec - 20 - 1967

Comment

GENERAL INFORMATION: This product is a water solution containing the equivalent of 5.32 lbs. ammonium sulfate per gallon. It is highly effective for killing undesirable woody plants and for use as a contact spray for control of weeds and grasses. Temporary non-productivity of soil may be caused by heavy application of the product; this condition usually disappears in the "over-winter" period.

Some species of woody plants and perennial weeds are difficult to control, and retreatment may be necessary if regrowth occurs. This product is water soluble, non-volatile, non-flammable. It is non-selective; do not apply to, or drain, or flush equipment on desirable plants or vegetation.

SPRAY PREPARATION:

WATER SOLUTION - For each 100 gals. of spray: Use 10 gals. product with hydraulic equipment: Use 18 to 72 gals. with air blast equipment.

OIL-WATER EMULSION ; For each 100 gals. of spray: With hydraulic equipment, use 9 gals. product plus a pre-mix (prepared in water free container) of 2/3 pt. emulsifying agent in 4 gals. of No. 2 fuel oil. Fill spray tank 1/2 full of water; start agitator, add product; add pre-mix, dilute to proper volume with water. For air blast equipment, use 18 to 40 gals. product plus pre-mix of 1 qt. emulsifying agent in 4 gals. of No. 2 fuel oil; prepare spray mixture as above.

DIRECTIONS - WEED AND GRASS CONTROL

TENNIS COURTS - DRIVEWAYS - FENCE ROWS - INDUSTRIAL SITES

- SUPER WEED & BRUSH CONTROL
Applied as a water solution or as an oil-water emulsion, is an effective contact spray for control of woody perennials such as poison ivy, poison oak, and poison sumac; perennials such as leafy spurge, bitter dock, goldenrod, perennial ragweed, milkweed, and blueweed; and annuals such as crabgrass, broomweed, chickweed, cocklebur, jimson weed, lambs quarters, larkspur, prickly lettuce, ragweed and shepherd's purse.

Use at rate of 18 gals. product per 100 gals. spray, either as water solution or as oil-emulsion. Prepare respective spray mixture as directed under "Brush-Control" for hydraulic equipment. Thoroughly wet foliage and stems of undesired vegetation. The degree of control and duration of effect will vary with weed species, rainfall, temperature, and other conditions.

SIDE PANEL

DIRECTIONS - BRUSH CONTROL

* RIGHT OF WAYS - ROADSIDES - DRAINAGE DITCHES - RANGELANDS - PASTURES

SUPER WEED & BRUSH CONTROL, applied as a foliage spray, is highly effective for killing most woody plants, including hard wood and coniferous species such as ash, birch, cedar, elm, gum, hickory, maple, oak, pine, and willow.

FOLIAGE SPRAY APPLICATION

Prepare spray (water solution or oil-water emulsion), and apply any time after brush has reached the full-leaf stage until foliage begins to discolor, preferably during periods of high temperatures and high humidity. Apply as a full-coverage spray to foliage stems, limbs, and base of brush; thorough coverage is essential for best results. In roadside applications on tall, dense brush, it is often necessary to spray from field side as well as road side. Spraying away from crops planted close to right-of-ways will aid in preventing contact of crops with spray or drift; coarse sprays are less likely to drift. The product is not volatile.

IMPORTANT: Wash sprayer thoroughly after use to remove all herbicidal solution and to reduce corrosion. Use of this product as an oil-water emulsion minimizes corrosion of equipment. If oil-water emulsion is not used, commercial equipment should be coated with an asphaltic base paint; or thoroughly wash exterior of equipment at end of each day and apply protective coating of oil each week or as often as practical. When equipment is down for week-end, wash exterior and coat with oil; for end-of-season storage, wash inside and outside and coat with oil. Do not reuse empty container. Wash thoroughly with water and detergent. Discard in a safe place.

11 Lbs. / Gal. @ 60 ° F.

