

GAS Oil

**HEAVY-DUTY
COATINGS**

**5536 Coastal Red
Anti-Fouling Paint**

CAUTION! KEEP OUT OF REACH OF CHILDREN.
HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL.

See back panel for additional cautions (FS-1)

USDA Reg.
No. 9855-14

NET ONE GALLON

**5536 COASTAL RED
ANTI-FOULING PAINT
Pigment 57.2%**

*Copper Pigment	40.8%
Magnesium Silicates	7.9%
Zinc Oxide	8.8%
Iron Oxide**	1.7%
**Ferric Oxide	84.0%
**Magnesium Silicates	16.0%

Vehicle 42.8%

Aliphatic Hydrocarbons	8.0%
Butyl Alcohol	.5%
Copper Naphthenate	1.4%

100.0%

**ANTI-FOULING INGREDIENTS
ACTIVE INGREDIENTS**

*Cuprous Oxide	38.7%
*Metallic Copper	.5%
Copper Naphthenate	1.4%
INERT INGREDIENTS	59.1%

4-9-70 100.0%
Total Copper Calculated as Metallic 85.3%

ANTI-FOULING
best performance

Surface Preparation:
Steel must be
antifouling.

Mixing: Before
intervals during

Application: A

Thinning: Thin
or 7076 Thinn

Coverage: Th
less dependi

Dry Time: At
of 4 hours be

Keep away
of a dwelling
or other furn
mist or repe
or smoking.