

Mobil[®] Marine Coating

PTED

NET 1 GALLON

ANTI-FOULING PAINT FOR METAL BOTTOMS:
 Appearance of two colors is considered the best performance.

Surface Preparation: Surface must be clean, dry and free of dirt, oil, grease, rust, old paint and other contaminants. Shell must be kept wet with water until the primer is applied. Surface must be free of sand and dirt.

Mixing: Before use, power mix for five minutes. This is important to insure proper dispersion of the pigments.

Application: Apply with brush or spray. Do not allow to dry too fast.

Thinning: Thin with water to a consistency of 2:1 for brush application.

Coverage: A 2 mil film will be obtained at a theoretical coverage of 345 sq. ft. per gallon per surface depending on the type of surface used. Actual coverage will be less due to application method, surface condition and condition of surface.

Dry Time: 24 hours to 48 hours depending on temperature and humidity.

Safety: Avoid contact with eyes, skin and clothing. Wash thoroughly with soap and water.

Caution: Do not use in confined spaces. Do not breathe vapors. Do not use in areas where fire or explosion is a hazard.

CONTAINS — ORGANIC SOLVENT

WARNING!



Flammable liquid and vapor.

Keep away from heat, open flames, sparks and other sources of ignition. Do not use in areas where fire or explosion is a hazard.

Do not breathe vapors. Do not use in areas where fire or explosion is a hazard.

Do not use in areas where fire or explosion is a hazard.

Do not use in areas where fire or explosion is a hazard.

Mobil Chemical Company
 MAINTENANCE & MARINE COATINGS DEPARTMENT
 LUDLOW, N.J. 08817, BEAUMONT, TEX. 77704, KENNESAW, WASH. 98148, LOS ANGELES, CALIF. 90048

Mobil

Vinyl Anti-Fouling Paint Dark Red 59-R-25

| | |
|--|--------|
| VINYL ANTI-FOULING PAINT DARK RED 59-R-25 | |
| ANTI-FOULING INGREDIENTS | |
| ACTIVE INGREDIENTS | |
| Cuprous Oxide | 51.4% |
| Metallic Copper | 1.1% |
| INERT INGREDIENTS | |
| 1-4-74 | 100.0% |

WARNING! See caution elsewhere
on label. (FR-6)

NOTICE: THIS PRODUCT IS FOR INDUSTRIAL USE ONLY
(FR-1) AND IS NOT INTENDED OR SUITABLE FOR USE
IN OR AROUND A HOUSEHOLD OR DWELLING.

EPA Reg. No. 9855-23

EPA Est. 9855-NJ-1

NET 1 GALLON

Mobil Chemical Company

ANTIFOULING PAINTS (FR-1) (FR-6)

CAUTION

FR-1

FR-6

FR-6

WARNING

