

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats.

Mixing: Before use, pour mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply by brush, roller or spray. Do not paint in cold or damp weather. When used over epoxy base coats, the first coat of anti-fouling should be applied while the epoxy is still in a

soft, uncured condition, typically, within 12-16 hours at 75°F (24°C). When this is not practical, apply a tie-coat of 80-A-8 Vinyl Primer, or 81 Series Hi-Build Vinyl within this interval. Anti-fouling may then be applied at any later time. **Thinning:** Thin slightly with Thinner 7-Y-37 when required for application. Use Thinner 7-Y-37 for clean up.

Coverage: Apply at a rate that will provide a 2 mil dry film per coat, theoretically 350 sq. ft. per gallon. Actual coverage will vary depending upon application technique, job conditions and type of surface.

Dry Time: At 75°F and 50% R.H., allow at least 4 hour dry time between coats, and a minimum of 8 hours before refloating. Where exposed to direct sunlight or high temperatures, launching is recommended no more than 24 hours after application.

STORAGE AND DISPOSAL:

PESTICIDE DISPOSAL: Pesticide, spray mixture or rinsate that cannot be used according to label instructions, must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

14-115 9-82

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (S2-1)**

CONTAINS ORGANIC SOLVENT

WARNING!

FLAMMABLE
CAUSES EYE IRRITATION
HARMFUL IF ABSORBED THROUGH SKIN.
Avoid contact with skin, eyes, or clothing.
Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat.
May be fatal if swallowed or inhaled.
Do not breathe vapor.
When used in enclosed areas, spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and National Institute for Occupational Safety and Health.
Remove contaminated clothing and wash before reuse.
Wash thoroughly with soap and water after handling.



PRACTICAL TREATMENT:

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Do not induce vomiting. Get medical attention.
If in eyes: Flush with plenty of water. Get medical attention.
If on skin: Wash with plenty of soap and water. Get medical attention.
If inhaled: Remove victim to fresh air. In not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

SHIPPING NAME: PAINT
HAZARD CLASS: FLAMMABLE LIQUID
HAZARD IDENTIFICATION NUMBER: UN1263
*Refer to product material safety data bulletin, available upon request, for further safety and handling information. (BCL-6 82)

Mobil® Marine Coat

Vinyl Anti-Fouling Paint Dark Brown 59-D-22

**KEEP OUT OF REACH OF CHILDREN
WARNING! See Precautions Elsewhere on**

For Industrial Use Only. Do Not Use In or
Around a Household or Dwelling. (S2-11)
Not Sold For Use In Air Pollution Regulation Areas.
Photochemically Reactive Per Rule 102. (S2-21)

EPA Reg. No. 9855-22

EPA Est.

NET 5 GAL. (18.927 L)

DOCUMENT AVAILABLE
9855-22

Mobil® Anti-Fouling Coating

Anti-Fouling Paint Brown 59-D-22

OUT OF REACH OF CHILDREN

See Precautions Elsewhere on Label

Industrial Use Only. Do Not Use in or
Household or Dwelling. (FR-11)
For Use in Air Pollution Regulation Areas.
Chemically Reactive Per Rule 102. (FR-21)

9855-22 EPA Est. 9855-N.J.-1

5 GAL. (18.927 Liters)

VINYL ANTI-FOULING PAINT DARK BROWN 59-D-22	
ANTI-FOULING INGREDIENTS	
ACTIVE INGREDIENTS	
Cuprous Oxide	51.8%
Metallic Copper	1.1%
INERT INGREDIENTS	47.1%
98-73	100.0%

BEST DOCUMENT AVAILABLE



Mobil Chemical Company
MAINTENANCE & MARINE COATINGS DEPARTMENT
EDISON, N.J. 08817/BEAUMONT, TEX. 77704/KANKAKEE, ILL. 60001/LOS ANGELES AREA/AZUSA, CALIF. 91702