

Mobil[®]

Marine Coating

ANTI FOULING PAINT FOR METAL BOTTOMS:

Application of two coats is recommended for best performance.

Surface Preparation: Surfaces must be dry, clean, and free of dirt, dust, grease, oil, rust, loose paint and other contaminants. Steel must be coated with suitable primer, or anti-corrosive barrier coats before application of anti-fouling.

Mixing: Before use, power mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply to fresh, dry or wet. Do not paint in cold or stormy weather.

Thinning: Thin with Mobil Thinner T-37 when required for application. Use Thinner T-37 for clean-up.

Coverage: A 2 mil dry film will be obtained theoretical spreading rate of 345-377 square per gallon, depending on the specific product used. Actual coverage will be less due to application techniques, job conditions and curvature of surface.

Dry Time: At 70°F and 50% R.H., allow a 4 hour dry time between coats, and a min of 8 hours before refloating.

Safety: When applied in confined areas, provide fresh air ventilation. Use fresh air and explosion proof electrical equipment.

Caution: Do not breathe vapors. Do not properly clean and when empty. Do not discharge water by cleaning of equipment used to apply.

CONTAINS — ORGANIC SOLVENT

WARNING!

FLAMMABLE LIQUID AND SOLID
VAPORS
See MSDS for details



Keep away from heat, sparks, and open flame.
Avoid breathing vapors.
Avoid contact with eyes, skin, and clothing.
Wash thoroughly after handling.

Use with adequate ventilation.
Wear an approved mask to avoid breathing concentrated vapors in enclosed areas.
Keep containers closed.

FIRST AID: If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If swallowed, do not induce vomiting. If on skin, wash with plenty of water.

If you are exposed to these vapors, you may experience irritation of your eyes, nose, and throat.

NET 1 GALLON

Mobil Chemical Company

MAINTENANCE & MARINE COATINGS DEPARTMENT
EDISON, N. J. 08817/BFAUMONT, TEX. 77704/KANKAKEE, ILL. 60901/LOS ANGELES, CALIF. 90058

Mobil

Coastal Super Service Anti-Fouling 59-R-7

COASTAL SUPER SERVICE ANTI-FOULING 59-R-7	
ANTI-FOULING INGREDIENTS	
ACTIVE INGREDIENTS	
Cuprous Oxide	47.6%
Metallic Copper	1.0%
INERT INGREDIENTS	81.5%
R-15-78	100.0%

WARNING! See caution elsewhere
on label. (FR-6)

NOTICE: THIS PRODUCT IS FOR INDUSTRIAL USE ONLY
(FR-1) AND IS NOT INTENDED OR SUITABLE FOR USE
IN OR AROUND A HOUSEHOLD OR DWELLING.

EPA Reg. No. 9855-25

EPA Est. 9855-NJ-1

NET 1 GALLON

WARNING



Mobil Chemical Company