

Mobil[®] Marine Coating

Vinyl Anti-Fouling Paint
Red 59-R-24

KEEP OUT OF REACH OF CHILDREN

WARNING! See Precautions Elsewhere on Label

For Industrial Use Only. Do Not Use In or
Around a Household or Dwelling. 99-111
Not Sold For Use In Air Pollution Regulation Areas. 99-211
Photochemically Reactive Per Rule 102. 99-211

EPA Reg. No. 9855-24

EPA Est. 9855-N.J.-1

NET 5 GAL. (18.927 Liters)



MILITARY ANTI-FOULING PAINT	
MIL-STD-1316	
ANTI-FOULING INGREDIENTS	
ACTIVE INGREDIENTS	
Copper Oxide	41.8%
Basic Copper	4.9%
INERT INGREDIENTS	53.3%
P-6-72	100.0%



Mobil Chemical Company

MAINTENANCE & MARINE COATINGS DEPARTMENT
EDISON, N.J. 07032/BEAUMONT, TEX. 77704/KANKAKEE, ILL. 60001/LOS ANGELES AREA/AZUSA, CALIF. 91032

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on metal bottoms in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coat.

Mixing: Before use pour air or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply by brush, roller or spray. Do not paint in cold or damp weather.

Thinning: Thin slightly with Thinner 7-Y-33 when required for application. See Thinner 7-Y-33 for clean-up.

Coverage: Apply at a rate that will provide a 1 mil dry film per coat, theoretically 433 sq. ft. per gallon. Actual coverage will vary depending upon application technique, job conditions and type of surface.

Dry Time: At 75°F and 50% R.H., allow at least 1 hour dry time between coats, and a minimum of 4 hours before refloating. Where exposed to direct sunlight or high temperatures, launching is recommended no more than 24 hours after application.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Pesticides, spray mixtures or residues that cannot be used according to label instructions, must be disposed of according to Federal, or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

MS-320 9-82

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (SA-1)**

CONTAINS ORGANIC SOLVENT

WARNING!

FLAMMABLE

CAUSES EYE IRRITATION

HARMFUL IF ABSORBED THROUGH SKIN.

Avoid contact with skin, eyes, or clothing

Wear protective clothing such as gloves, long-sleeved

cotton shirt, long pants, and hat

May be fatal if swallowed or inhaled

Do not breathe vapor

When used in enclosed areas, spraying paint or sanding

boat surface, wear a respirator jointly approved by the

Mining Enforcement and Safety Administration and the

National Institute for Occupational Safety and Health

Remove contaminated clothing and wash before reuse

Wash thoroughly with soap and water after handling



PRACTICAL TREATMENT:

If swallowed, Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes, Flush with plenty of water. Get medical attention.

If on skin, Wash with plenty of soap and water. Get medical attention.

If inhaled, Remove victim to fresh air. In not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

SHIPPING NAME: PAINT

HAZARD CLASS: FLAMMABLE LIQUID

HAZARD IDENTIFICATION NUMBER: UN1263

*Refer to product material safety data bulletin, available upon request, for further safety and handling information.

(BCL-84 8-82)