

Mobil[®] Marine Coating

Coastal Super Service Anti-Fouling 59-R-7

KEEP OUT OF REACH OF CHILDREN

WARNING! See Precautions Elsewhere on Label (P-27)

For Industrial Use Only. Do Not Use In or
Around a Household or Dwelling. (P-11)
Not Sold For Use In Air Pollution Regulation Areas.
Photochemically Reactive Per Rule 102. (P-21)

EPA Reg. No. 9855-25

EPA Est. 9855-NJ-1

NET 5 GAL. (18.927 Liters)

BEST DOCUMENT AVAILABLE

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment. Disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Disposal of paint sludge in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL SURFACES: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would retard growth. Not recommended for use on aluminum. A system of two coats is recommended for best results.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be treated with a suitable primer or anti-corrosive prior to use.

Mixing: Before use power mix or mix the paint until the product is uniform. Stir the paint during application to maintain uniformity.

Application: Apply by brush, roller or spray. Do not paint in cold or damp weather. The epoxy base coats, the first coat of anti-fouling should be applied while the epoxy is still in a wet

condition, typically, within 12-18 hours at 75°F (24°C). When this is not practical, apply a tie-coat of E3-R-2 Vinyl Primer, or E3 Isocel Hi-Build Vinyl within this interval. Anti-fouling may then be applied at any later time.

Thinning: Thin slightly with Thinner T-7-37 when required for application. Use Thinner T-7-37 for clean up.

Coverage: Apply at a rate that will provide a 2 mil dry film per coat, theoretically 640 sq. ft. per gallon. Actual coverage will vary depending upon application technique, job conditions, and type of surface.

Dry Time: At 75°F and 50% R.H., allow at least 1 hour dry time between coats, and a minimum of 8 hours before refloating. Where exposed to direct sunlight or high temperatures, leaching is recommended no more than 24 hours after application.

STORAGE AND DISPOSAL:

PESTICIDE DISPOSAL: Pesticide, spray mixture or residue that cannot be used according to label directions must be disposed of according to Federal, or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

MS-370 9-82

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS (28-1)

CONTAINS ORGANIC SOLVENT
WARNING!

FLAMMABLE
CAUSES EYE IRRITATION
HARMFUL IF ABSORBED THROUGH SKIN
Avoid contact with skin, eyes, or clothing
Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat
May be fatal if swallowed or inhaled
Do not breathe vapor

When used in enclosed areas, spraying paint or sanding boat surfaces, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health
Remove contaminated clothing and wash before reuse
Wash thoroughly with soap and water after handling



PRACTICAL TREATMENT:

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.
If in eyes: Flush with plenty of water. Get medical attention.
If on skin: Wash with plenty of soap and water. Get medical attention.
If inhaled: Remove victim to fresh air. In not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

SHIPPING NAME: PAINT
HAZARD CLASS: FLAMMABLE LIQUID
HAZARD IDENTIFICATION NUMBER: UN1263
*Refer to product material safety data bulletin, available upon request, for further safety and handling information.
(SCL-84 6-82)