

Mobil®
Marine Coating

Vinyl Anti-Fouling Paint
MIL-P-16189 (Formula 129/63)
Black 559-J-1

KEEP OUT OF REACH OF CHILDREN

9855-28


WARNING! See Precautions Elsewhere on Label (FR-22)

For Industrial Use Only. Do Not Use in or
Around a Household or Dwelling. (FR-11)
Not Sold For Use in Air Pollution Regulation Areas.
Photochemically Reactive Per Rule 102. (FR-21)

EPA Reg. No. 9855-28

EPA Est. 9855-N.J.-1

NET 5 GAL. (18.927 Liters)



| | |
|--------------------------|--------|
| ANTI-FOULING INGREDIENTS | |
| ACTIVE INGREDIENTS | |
| Copper Oxide | 60.0% |
| Metallic Copper | 1.3% |
| INERT INGREDIENTS | 38.7% |
| Mob-Jet 3-11-74 | 100.0% |



Mobil Chemical Company

MAINTENANCE & MARINE COATINGS DEPARTMENT
EDISON, N.J. 08807/BEALMONT, TEX. 77704/KANKAKEE, ILL. 60901/LOS ANGELES AREA/AZUSA, CALIF. 91702 421

DIRECTIONS FOR USE

✓ It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. For commercial use only.

| | |
|-------------------------------|---|
| CLASSIFICATION: | Vinyl |
| USES: | Anti-fouling protective coating for use in salt water environments to control the growth of barnacles and other common marine fouling organisms. Use over properly prepared and primed steel, wood, aluminum, ferro-cement or fiberglass marine structures and ships hulls. |
| FINISH: | Flat |
| COLOR: | Red |
| COMPONENTS: | One |
| SURFACE PREPARATION: | Paint only clean, dry surfaces. For new work, apply one or two coats over recommended Napko Epoxy or Coal Tar Epoxy anti-corrosive bottom systems. For refresher coats, sweep blast or water blast old coating to remove all marine growth, surface contamination and loose or peeling coating. Spot prime as required with recommended Napko Epoxies and apply one or two coats. |
| MIXING AND THINNING: | Stir until thoroughly mixed. Thin as required up to 10% by volume with Napko 222 Thinner. |
| APPLICATION: | Air or airless spray; brush for touch-up. |
| DRYING TIME: | To Touch-4 hours To Recoat-16 to 24 hours To Launch-24 hours |
| COVERAGE: | 144 sq. ft./gal./mil (25 μ m) |
| RECOMMENDED THICKNESS: | Wet-7.5-11.0 mils (185-275 μ m) Dry-2.0-3.0 mils (50-75 μ m) |
| WEIGHT PER GALLON: | 18.6 lbs. (4.1 kg) |
| FLASH POINT: | 61°F (16°C) |
| CLEAN-UP THINNER: | Napko 222 Thinner |

STORAGE AND DISPOSAL

Storage-Do not store near heat, sparks or open flame. Keep closures tight and upright to prevent leakage. Keep container closed when not in use. In case of spillage, absorb with sawdual or disposable rags and flush with large volumes of water.

Disposal-Anti-fouling coating, thinning and clean-up solvents, clean-up materials or rinsate that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act. Do not reuse containers. Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

PAINT



THE O'BRIEN CORPORATION
South San Francisco, CA 94080

FOR INDUSTRIAL USE ONLY

DATA
10 700

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS DANGER

Corrosive Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes or on clothing. Wear goggles or face shield. Wear protective clothing such as long sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor, spray mist, or dust or chips from surface preparation. While spraying or abrading coated surfaces wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health. Use with adequate ventilation.

ENVIRONMENTAL HAZARDS

This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS

Flammable Keep away from heat, and open flame.

BEST DOCUMENT AVAILABLE