

BEST PRODUCT AVAILABLE

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Flammable. Keep away from heat and open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would sustain such growth.

Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats.

Mixing: Before use, power mix paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply by brush, roller or spray. Do not paint in cold or damp weather.

Thinning: Thin slightly with Thinner 7-T-33 or Xylene (TI-X-916) when required for application.

Use same Thinner for clean up.

Coverage: Apply at a rate that will provide a 2 mil dry film per coat, theoretically 575 sq. ft. per gallon. Actual coverage will vary depending upon application technique, job conditions and type of surface.

Dry Time: At 75°F and 50% R.H., allow at least 2 hour dry time between coats, and a minimum of 4 hours before refloating. Where exposed to direct sunlight or high temperatures, launching is recommended no more than 24 hours after application.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Pesticide, spray mixture or rinsate that cannot be used according to label instructions, must be disposed of according to Federal, or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

ML-328

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (SA-1)

CONTAINS ORGANIC SOLVENT

WARNING!

FLAMMABLE.

CAUSES EYE IRRITATION.

HARMFUL IF ABSORBED THROUGH SKIN.

Avoid contact with skin, eyes, or clothing.

Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat.

May be fatal if swallowed or inhaled.

Do not breathe vapor.

When used in enclosed areas, spraying paint or sanding boat surface, wear a respirator jointly approved by the

Mining Enforcement and Safety Administration and the

National Institute for Occupational Safety and Health.

Remove contaminated clothing and wash before reuse.

Wash thoroughly with soap and water after handling.



PRACTICAL TREATMENT:

If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. In not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

SHIPPING NAME:

HAZARD CLASS:

HAZARD IDENTIFICATION NUMBER: UN1263

"Refer to product material safety data bulletin, available upon request, for further safety and handling information."

(BCL-84 6-82)

PAINT

FLAMMABLE LIQUID

Mobil®

Marine Coat

Shipbottom Paint

✓ Cold Plastic Anti-Foul MIL-P-19451 (Formula

559-R-1

KEEP OUT OF REACH OF CHILDREN
WARNING! See Precautions Elsewhere on Label

For Industrial Use Only. Do Not Use In or
Around a Household or Dwelling. (PA)
Not Sold For Use In Air Pollution Regulation Areas (PA)
Photochemically Reactive Per Rule 102. (PA)

EPA Reg. No. 9855-29

EPA Est

NET 5 GAL. (18.927 L

Mobil®

ie Coating

ottom Paint

stic Anti-Fouling

51 (Formula 105)

559-R-1

UT OF REACH OF CHILDREN

ee Precautions Elsewhere on Label (FR-22)

trial Use Only. Do Not Use In or
Household or Dwelling. (FR-11)
or Use In Air Pollution Regulation Areas.
nically Reactive Per Rule 102. (FR-21)

855-29 EPA Est. 9855-N.J.-1

GAL. (18.927 Liters)

ANTI-FOULING INGREDIENTS		
ACTIVE INGREDIENTS		
Cuprous Oxide	30.4%	
Metallic Copper	7.0%	
INERT INGREDIENTS		
559-R-1	3-11-74	100.0%

DOCUMENT AVAILABLE



Mobil Chemical Company

MAINTENANCE & MARINE COATINGS DEP. IENT
EDISON, N.J. 08817/BEAUMONT, TEX. 77704/KANKAKEE, ILL. 60801/LOS ANGELES AREA/AZUSA, CALIF. 91702