

ANTI-FOULING PAINT FOR METAL BOTTOMS:

Application of two coats is recommended for best performance.

Surface Preparation: Surface must be dry, clean, and free of dirt, dust, grease, oil, rust, loose paint and other contaminants. Steel must be coated with a suitable primer or anti-rust primer before application of antifouling.

Mixing: Before use, power mix or box the paint thoroughly to break down the pigments and fillers.

Application: Apply by brush, spray or roller. Do not paint in cold or damp weather.

Thinning: Thin if necessary with Thinner 7-T-35 when required for application of Thinner 7-T-35 for clean-up.

CONTAINS ORGANIC IN COMPOUND
AND ORGANIC SOLVENT

WARNING!

FLAMMABLE (F+100°F/TCC).

HARMFUL IF SWALLOWED OR ABSORBED
THROUGH SKIN.

CAUTION: IRRITANT.

CAUTION: IRRITANT.

Keep away from heat, sparks, open flames, and other sources of ignition.

Do not breathe vapors or dusts. Avoid contact with skin and eyes.

Use only with adequate ventilation. Wear an air supplied mask to avoid breathing concentrated vapors in enclosed areas.

Keep container closed.



Coverage: A 1 mil dry film will be obtained at a theoretical spreading rate of 34-37 square feet per gallon, depending on the specific product used. Actual coverage will be less due to application technique, surface conditions and condition of surface.

Dry Time: At 70°F and 50% RH, dry to touch in 4 hour; dry to handle in 24 hours; and a film of 8 mils in 7 days.

Safety: Use only with adequate ventilation. Wear an air supplied mask to avoid breathing concentrated vapors in enclosed areas. Keep container closed.

Caution: Do not reuse container. Do not pour or properly dispose of empty container. Do not contaminate water by cleaning of equipment or disposal of wastes.

Use with adequate ventilation.

Wear an air supplied mask to avoid breathing concentrated vapors in enclosed areas.

Keep container closed.

FIRST AID: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. Call a physician.

In case of contact with skin, remove clothing and wash with plenty of water. If contact with eyes, flush with plenty of water. If swallowed, do not induce vomiting. Call a physician.



Mobil Chemical Company