



Mobil[®] Marine Coc Vinyl Anti-Fouling Black 559-J-4

KEEP OUT OF REACH OF CHILDREN
DANGER! See Precautions Elsewhere

For Industrial Use Only. Do Not Use In or
Around a Household or Dwelling.
Not Sold For Use In Air Pollution Regulation Area
Photochemically Reactive Per Rule 102.

EPA Reg. No. 9855-30 EPA

NET 5 GAL. (18.927

BEST DOCUMENT

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in a approved landfill.

PHYSICAL OR CHEMICAL HAZARDS: Do not use or store near heat or open flame.

DIRECTIONS FOR USE: It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

ANTI-FOULING PAINT FOR METAL AND FIBERGLASS BOTTOMS: To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., in salt, brackish, and fresh water which would sustain such growth. A minimum of two coats are recommended for best performance.

Surface Preparation: Before application of anti-fouling, all surfaces must be dry, and cleaned of dirt, dust, oil, rust, loose paint, salt deposits, and other contaminants. Bare metal must be coated with a suitable primer, or anti-corrosive barrier coats. Bare fiberglass must be abraded, by sanding or other means, to a dull finish with a slight surface roughness.

Mixing: Before use, power mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

Application: Apply by spray. Do not paint in cold or damp weather.

Thinning: Thin slightly with Thinner 7-T-37 when required for application. Use Thinner 7-T-37 for clean-up.

Coverage: Apply at a rate that will provide a 3 mil dry film per coat, theoretically 180 sq. ft. per gallon. Actual coverage will vary depending upon application technique, job conditions and type of surface.

Dry Time: At 75°F and 50% R.H., allow at least 4 hour dry time between coats, and a minimum of 8 hours before refloating.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Pesticide, spray mixture or rinsate that cannot be used according to label instructions must be disposed of according to Federal, or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

ML-329 8-81

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (SR-1)

CONTAINS ORGANO TIN COMPOUND
AND ORGANIC SOLVENT

DANGER!

FLAMMABLE.
CORROSIVE
VAPOR HARMFUL.
CAUSES SEVERE SKIN AND EYE DAMAGE.

Do not get on skin, clothing or in eyes. Wear a face shield and rubber gloves when handling. Harmful if swallowed or inhaled. Use in well ventilated area. Wash thoroughly after handling. Keep container closed.

When used in enclosed areas, spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

FIRST AID:

If in eye: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.


If swallowed: Do not induce vomiting. The product contains petroleum distillates. Get immediate medical attention.

If inhaled: Remove to fresh air. Use artificial respiration if breathing has stopped. Get immediate medical attention.

Shipping Name: Paint
Hazard Class: Flammable Liquid
Hazard Identification Number: UN1263

"Refer to product material safety data bulletin, available upon request, for further safety and handling information."
(BCL-61 7-82)

BEST DOCUMENT AVAILABLE



Mobil[®] Marine Coating

Vinyl Anti-Fouling Paint Black 559-J-4

KEEP OUT OF REACH OF CHILDREN
DANGER! See Precautions Elsewhere on Label (PA-21)

For Industrial Use Only. Do Not Use in or
Around a Household or Dwelling. (PA-11)
Not Sold For Use in Air Pollution Regulation Areas.
Photochemically Reactive Per Rule 102. (PA-21)

EPA Reg. No. 9855-30 EPA Est. 9855-N.J.-1

NET 5 GAL. (18.927 Liters)

BEST DOCUMENT AVAILABLE

9855-30

ANTI-FOULING INGREDIENTS
ACTIVE INGREDIENTS
Tri-n-butyltin Fluoride 17.75%
Bis(tri-n-butyltin) Oxide 3.92%
INERT INGREDIENTS 78.33%
Total 100.00%
Total Tin Content 8.43%
59-16 5-13-82



Mobil Chemical Company
MAINTENANCE & MARINE COATINGS DEPARTMENT
EDISON, N.J. 08817/BEAUMONT, TEX. 77704/KANKAKEE, ILL. 60901/LOS ANGELES AREA

BEST DOCUMENT AVAILABLE



Mobil® e Coating

i-Fouling Paint
ck 559-J-4

OF REACH OF CHILDREN

Precautions Elsewhere on Label (FR-22)

Use Only. Do Not Use In or
ehold or Dwelling. (FR-11)
e In Air Pollution Regulation Areas.
y Reactive Per Rule 102. (FR-21)

855-30 EPA Est. 9855-N.J.-1

AL. (18.927 Liters)

BEST DOCUMENT AVAILABLE

9855-30

ANTI-FOULING INGREDIENTS
ACTIVE INGREDIENTS
Tri-n-butyltin Fluoride 17.75%
Bis(tri-n-butyltin) Oxide 3.92%
INERT INGREDIENTS 78.33%
Total 100.00%
Total Tin Content 8.43%
59-16 5-13-82



Mobil Chemical Company

MAINTENANCE & MARINE COATINGS DEPARTMENT
EDISON, N.J. 08877/BEAUMONT, TEX. 77704/KANKAKEE, ILL. 60901/LOS ANGELES AREA/AZUSA, CALIF. 91702

