

**ENVIRONMENTAL HAZARDS:** This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

**PHYSICAL OR CHEMICAL HAZARDS:** Flammable. Keep away from heat and open flame.

**DIRECTIONS FOR USE:** It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**ANTI-FOULING PAINT FOR METAL BOTTOMS:** To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

**Surface Preparation:** Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coat.

**Mixing:** Before use power mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

**Application:** Apply by brush, roller or spray. Do not paint in cold or damp weather.

**Thinning:** Thin slightly with Thinner 7-T-33 when required for application. Use Thinner 7-T-33 for clean up.

**Coverage:** Apply at a rate that will provide a 2 mil dry film per coat, theoretically 328 sq. ft. per gallon. Actual coverage will vary depending upon application technique, job conditions and type of surface.

**Dry Time:** At 75°F and 50% R.H., allow at least 4 hour dry time between coats, and a minimum of 8 hours before refloating. Where exposed to direct sunlight or high temperatures, launching is recommended no more than 24 hours after application.

**STORAGE AND DISPOSAL:**

**PESTICIDE DISPOSAL:** Pesticide, spray mixture or mixture that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or burn and dispose of in a sanitary landfill, or by other approved state and local procedures.

MA-330 9-82

#### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (28-1)

CONTAINS ORGANO TIN COMPOUND  
AND ORGANIC SOLVENT

#### DANGER!

FLAMMABLE.  
CORROSIVE.  
VAPOR HARMFUL.  
CAUSES SEVERE SKIN AND EYE DAMAGE.



Do not get on skin, clothing or in eyes. Wear a face shield and rubber gloves when handling. Harmful if swallowed or inhaled. Use in well ventilated area. Wash thoroughly after handling. Keep container closed.

When used in enclosed areas, spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

#### FIRST AID:

**If in eyes:** Flush with plenty of water. Get medical attention.

**If on skin:** Wash with plenty of soap and water. Get medical attention.

**If swallowed:** Do not induce vomiting. The product contains petroleum distillates. Get immediate medical attention.

**If inhaled:** Remove to fresh air. Use artificial respiration if breathing has stopped. Get immediate medical attention.

Shipping Name: Paint  
Hazard Class: Flammable Liquid  
Hazard Identification Number: UN1263

"Refer to product material safety data bulletin, available upon request, for safety and handling information."  
(BCL-61 7-82)

# Mobil® Marine Coat

A Paint Product  
Sovaklor  
Long Life  
Anti-Fouling 59-R-

KEEP OUT OF REACH OF CHILDREN  
**DANGER!** See Precautions Elsewhere on Label

For Industrial Use Only. Do Not Use In or  
Around a Household or Dwelling. (FR-11)  
Not Sold For Use In Air Pollution Regulation Areas.  
Photochemically Reactive Per Rule 102. (FR-21)

EPA Reg.No.9855-31

EPA Est. 98

NET 5 GAL. (18.927 Lite

# Mobil<sup>®</sup> e Coating

aint Product (FR-3)

ovaklor

ong Life

ouling 59-R-26

IT OF REACH OF CHILDREN

e Precautions Elsewhere on Label (FR-22)

rial Use Only. Do Not Use In or  
household or Dwelling. (FR-11)  
or Use In Air Pollution Regulation Areas.  
ically Reactive Per Rule 102. (FR-21)

55-31 | EPA Est. 9855-N.J.-1

AL. (18.927 Liters)

ANTI-FOULING INGREDIENTS		
ACTIVE INGREDIENTS		
Cuprous Oxide		45.30%
Metallic Copper		0.91%
Tri-n-butyltin Fluoride		3.90%
INERT INGREDIENTS		
59-R-26	11-27-78	100.00%



BEST DOCUMENT AVAILABLE

**Mobil Chemical Company**

MAINTENANCE & MACHINE COATINGS DEPARTMENT  
EDISON, N.J. 08817/BEAUMONT, TEX. 77704/KA DEE, ILL. 60801/LOS ANGELES AREA/AZUSA, CALIF. 91712