

**ENVIRONMENTAL HAZARDS:** This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

**PHYSICAL OR CHEMICAL HAZARDS:** Flammable. Keep away from heat and open flame.

**DIRECTIONS FOR USE:** It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**ANTI-FOULING PAINT FOR METAL BOTTOMS:** To control the attachment of marine fouling, i.e., barnacles, grass, algae, etc., on steel bottoms in salt and brackish water which would sustain such growth. Not recommended for use on aluminum. A minimum of two coats is recommended for best performance.

**Surface Preparation:** Before application of anti-fouling, all surfaces must be dry and cleaned of dirt, dust, oil, rust, loose paint, salt residues, and other contaminants. Steel must be coated with a suitable primer or anti-corrosive barrier coats.

**Mixing:** Before use pour mix or box the paint until the product is uniform. Stir the paint at intervals during application to maintain uniformity.

**Application:** Apply by brush, roll or spray. Contents may be applied by hot spray (temperature not to exceed 95°F), airless spray or regular cold spray. Apply a full wet coat in a double cross-

hatch pattern. Do not paint in cold or damp weather.

**Thinning:** Normally no thinning required. Where thinning is necessary, for Class 1 material use Thinner 7-Y-36 (methyl isobutyl ketone) where required by specification, or Thinner 7-Y-37 for commercial work. For Class 2 material use Thinner 7-Y-50 (n-butyl acetate) where required by specification, or Thinner 7-Y-45 for commercial work.

**Coverage:** A 2 mil dry film will be obtained at a theoretical coverage of 505 square feet per gallon for Type I (red) material, and 480 square feet per gallon for Type II (black) material. Actual coverage will be less due to application techniques, job conditions and condition of surface.

**Dry Time:** At 70°F and 50% R.H., allow at least 4 hour dry time between coats, and a minimum of 8 hours before refloating.

**STORAGE AND DISPOSAL:**

**PESTICIDE DISPOSAL:** Pesticide, spray mixture or ringon that cannot be used according to label instructions must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act.

**CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

ML-366 6-82

71913 34L

# Mobil

## Marine Co

### Vinyl Anti-Fouling

#### MIL-P-0015931D (Form 1)

#### Type II Class 1 Grade 1

#### Black 559-J

KEEP OUT OF REACH OF CHILDREN

**WARNING!** See Precautions Elsewhere

For Industrial Use Only. Do Not Use Around a Household or Dwelling. Not Sold For Use In Air Pollution Regulatory Areas. Photochemically Reactive For Rule 112.

EPA Reg. No. 9855-34

NET 5 GAL. (18.9 L)

BEST DOCUMENT AVAILABLE

### PRECAUTIONARY STATEMENTS

#### HAZARDS TO HUMANS (& DOMESTIC ANIMALS) (28-1)

CONTAINS ORGANIC SOLVENT.  
**WARNING!**  
**FLAMMABLE.**



CAUSES EYE IRRITATION.  
HARMFUL IF ABSORBED THROUGH SKIN.  
Avoid contact with skin, eyes or clothing.  
Wear protective clothing such as gloves, long-sleeved cotton shirt, long pants, and hat.  
May be fatal if swallowed or inhaled.  
Do not breathe vapor.  
When used in enclosed areas, spraying paint or sanding boat surface, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.  
Remove contaminated clothing and wash before reuse.

Wash thoroughly with soap and water after handling.  
**PRACTICAL TREATMENT:**  
**If swallowed:** Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.  
**If in eyes:** Flush with plenty of water. Get medical attention.  
**If on skin:** Wash with plenty of soap and water. Get medical attention.  
**If inhaled:** Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.  
**SHIPPING NAME:** PAINT  
**HAZARD CLASS:** FLAMMABLE LIQUID  
**HAZARD IDENTIFICATION NUMBER:** UN1263

\*Refer to product material safety data bulletin, available upon request, for further safety and handling information.\*

DCL-84 (4/82)

BEST DOCUMENT AVAILABLE

# Mobil® Anti-Fouling Coating

**Anti-Fouling Paint**  
**15931D (Formula 129)**  
**Class II Grade A**  
**Black 559-J-5**

**KEEP OUT OF REACH OF CHILDREN**

See Precautions Elsewhere on Label

FR-22

Industrial Use Only. Do Not Use in or  
near a Household or Dwelling. (FR-11)  
For Use in Air Pollution Regulation Areas.  
Chemically Reactive For Rule 102. (FR-21)

9855-34

EPA Est. 9855-NJ-1

GAL. (18.927 Liters)

DOCUMENT AVAILABLE



*Flammable DOT  
Diamond*

Pigment	71.7%
Cuprous Oxide Pigment	58.6%
Black Synthetic Iron Oxide	12.7%
Silicates	.4%
Vehicle	28.3%
Vinyl Resin	2.4%
Rosin	9.5%
Plasticizer	2.0%
Ketone	8.7%
Aromatic Hydrocarbons	5.6%
Propene Oxide	.1%
	100.0%

**ANTI-FOULING INGREDIENTS**

**ACTIVE INGREDIENTS**

Cuprous Oxide	55.70%
INERT INGREDIENTS	44.30%

Total 100.00%

559-1 7-21-81

**Mobil Chemical Company**

MAINTENANCE & MARINE COATINGS DEPARTMENT  
EDISON, N.J. 08817/BEAUMONT, TEX. 77704/KANKAKEE, ILL. 80901/LOS ANGELES AREA/AZUSA, CALIF. 91702