

JUL 15 1986

Technical Specialties Corporation
250 Arizona Avenue NE.
Atlanta, GA 30307

Attention: Carol F. DiRenzo, Agent

Gentlemen:

Subject: TSC-903
EPA Registration No. 9861-8
Your Submission Dated June 24, 1986

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. A stamped copy is enclosed for your records.

Note: The Agency will not be issuing another Registration Notice for the above product. Our letter dated July 9, 1986, by Art Donner is sufficient documentation to address your request to amend our records. However, the Agency will issue another stamped label for your files with the new EPA Registration Number.

Sincerely yours,

John H. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

Enclosure

90359:Lee:L-10:KENCO:7/11/86:7/22/86:DKD:LMF

CONCURRENCES

SYMBOL ▶								
SURNAME ▶								
DATE ▶								

1

2/2

TSC-903

REGISTERED

JUL 15 1981

ACTIVE INGREDIENTS:

registered under EPA Reg. No.

Methylene bis(thiocyanate)	9.861-8	10%
2-(Thiocyanomethylthio)benzothiazole		10%

INERT INGREDIENTS		80%
-------------------------	--	-----

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, causes irreversible eye damage and causes skin damage. Harmful or fatal if swallowed or absorbed through the skin. This product is a potential skin sensitizer. Workmen handling this product or treated material should wear impervious gloves, goggles or face shield, and protective clothing. All protective clothing, work shoes or boots, and equipment must be left at the work site at the end of the day. Eating, drinking, or smoking during use of this product is prohibited.

FIRST AID: *In case of skin contact*, wash promptly and thoroughly with soap and water and finally with glycerin. *If product gets in the eyes*, flush immediately with copious amounts of clean, cool water for 15 to 30 minutes. Get medical attention immediately. *If product is swallowed*, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. *Do not induce vomiting or give anything by mouth to an unconscious person.*

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

Manufactured by:
Technica! Specialities Corp.
250 Arizona Ave. NE
Atlanta, GA 30307

EPA REG. NO. _____ EPA Est. No. _____

NET CONTENTS: _____

DIRECTIONS FOR

It is a violation of Federal law to use this product in a

COOLING TOWERS: TSC-903 is used to protect cooling towers from internal or dry rot. It is applied by spraying or painting a dilute solution of TSC-903 in water onto the clean wood surfaces. The amount of TSC-903 per 1000 ft.² of wood surface. Soft or surface rot is treated with 2 doses of TSC-903 to the recirculating cooling water at the same time. This should provide 1.25 lb. of TSC-903 per 1000 gal. of water, a 6 hr. after treatment. The shock treatment should be repeated.

COOLING WATER: TSC-903 is used to control algae, bacteria, and fungi in cooling water systems. Before treatment is begun, the system should be flushed, refilled with water, and treated with an initial dose of 1.25 lb. gal. water in the system. Subsequent additions of 0.2 to 1.25 lb. gal. 1 to 5 days, depending on amount of bleedoff and severity of infestation.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of wells, TSC-903 is incorporated in the drilling fluid at a concentration of 1.25 lb. the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: TSC-903 is used to control bacteria and fungi in oil-field water, polymer, or other oil-field water systems at dosage rates of 1.2 to 4.0 lb. per 1000 gal. treated. Additions should be made continuously or intermittently to prevent free water knockouts, before or after injection pumps and separators.

Method: When system is noticeably fouled, add 1.2 to 4.0 lb. per 1000 gal. continuously until desired degree of control is achieved. Then add 1.25 lb. per 1000 gal. of water continuously, or as needed to maintain control. When system is noticeably fouled, or to maintain control, add 1.25 lb. of water for 4 to 8 hr. per day and 1 to 4 times per week.

CRUDE AND REFINED OILS: TSC-903 is an oil-soluble fungicide that causes the degradation of crude oil and refined fuels. It is used to control fungi that cause the degradation of the oil as it is being transferred from the shipping container to the storage tank. Add 1.25 fl. oz. TSC-903 per 1000 gal. of oil. Addition should be made continuously to the suction side of the transfer pump.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. **STORAGE:** Do not expose to extreme temperatures. Do not store in areas where it should be opened in well-ventilated areas. Leaking or damaged drums for disposal. Spills should be absorbed in sawdust or other inert material. **PESTICIDE DISPOSAL:** Pesticide wastes are acutely toxic. If a spill occurs, contact your State or Federal Pesticide Control Authority. If use according to label instructions, contact your State or Federal Pesticide Control Authority or the Hazardous Waste representative at your EPA Regional Office. **CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then puncture and dispose of in a sanitary landfill, by incineration, or other approved method, if incineration is required, contact local authorities, by burning. If burned, stay out of smoke.