



ACCEPTED
Apr - 2 - 1968

UNDER THE FEDERAL INSECTICIDE,
FUNGICIDE AND RODENTICIDE ACT
FOR ECONOMIC POISON REGISTERED
UNDER NO. *9868-4*

Common

ACCEPTED

APR 22 1958

INSTRUMENTS
REGISTERED
9F67-4 SUBJECT

DIRECTIONS:
USE ROLLER, BRUSH OR SPRAY
PAINT OVER DRY CLEAN SURFACES ONLY
ALLOW 1 TO 4 HOURS BETWEEN COATS
AND BEFORE ANCHORING

CAUTION! COMBUSTIBLE!
CONTAINS LEAD. HARMFUL IF SWALLOWED.
Keep away from heat and open flame. Do not apply on window sills, toys, furniture
or interior surfaces of rooms which may be used by children. Avoid prolonged con-
tact with skin and breathing of vapor or spray mist. Close container after each use.
Use with adequate ventilation. KEEP OUT OF THE REACH OF CHILDREN.

COMPLY WITH SIZE REGULATIONS WHEN PRINTED



GAS Oil

**HEAVY-DUTY
COATINGS**

**5537 Tropical Super Service
Anti-Fouling Paint**

NOTICE THIS PRODUCT IS FOR INDUSTRIAL USE ONLY
(FR-1) AND IS NOT INTENDED OR SUITABLE FOR USE
IN OR AROUND A HOUSEHOLD OR DWELLING.

EPA Reg. No. 9855-18 NET ONE GALLON EPA Est. 9855-TX-1

ANTI-FOULING PAINT FOR METAL BOTTOMS-
Application of two coats is recommended for
best performance.

Surface Preparation: Surfaces must be dry, clean,
and free of dirt, dust, grease, oil, rust, scale,
and other contaminants. Surfaces must be
cleaned with a suitable primer or anti-rust
paint before application of this paint.

Mixing: This paint is a two-part system. The
pigment and resin components must be
thoroughly mixed before use.

Application: Apply with brush, roller, or
sprayer. Apply in two coats.

Thinning: This paint is not intended to be
thinned. Thinning will reduce the
anti-fouling properties.

CONTAINS ORGANIC SOLVENTS

WARNING!

Flammable liquid
and vapor. May
be irritating to
eyes.



Keep away from heat, sparks, and open flame.
Avoid breathing vapors.
Avoid contact with eyes, skin, and clothing.
Wash thoroughly after handling.

Coverage: This paint is designed to provide
outstanding performance. A typical coverage
is 100 sq. ft. per gallon. Actual coverage will
vary with surface conditions.

Dry Time: This paint is designed to dry
quickly. A typical dry time is 24 hours.
Actual dry time will vary with surface
conditions.

Storage: This paint is designed to be
stored in a cool, dry place. It should
not be stored in a metal container.

Cleanup: This paint is designed to be
cleaned up with a suitable solvent.
Do not pour down the drain.

First Aid: In case of contact, remove
contaminated clothing. Flush with
plenty of water. Seek medical attention
if necessary. Call a physician.

First Aid: In case of contact, remove
contaminated clothing. Flush with
plenty of water. Seek medical attention
if necessary. Call a physician.

First Aid: In case of contact, remove
contaminated clothing. Flush with
plenty of water. Seek medical attention
if necessary. Call a physician.

**WARNING! See caution elsewhere
on label. (FR-6)**

Mobil Chemical Company

MAINTENANCE & MARINE COATINGS DEPARTMENT, P.O. BOX 1000, BEAUMONT, TEXAS 77701, U.S.A.