

DIRECTIONS FOR USE

Apply to the surface of the wood to be treated. Apply liberally to all surfaces. For best results, apply to the wood when it is dry. Do not apply to wet wood. Do not apply to painted or stained wood. Do not apply to wood that has been treated with a preservative. Do not apply to wood that has been treated with a preservative. Do not apply to wood that has been treated with a preservative.

NOT

Do not use on wood that is to be painted or stained. Do not use on wood that is to be treated with a preservative. Do not use on wood that has been treated with a preservative. Do not use on wood that has been treated with a preservative.

STORAGE and DISPOSAL

Store in a cool, dry place. Do not store in a hot or cold place. Do not store in a place where the temperature is above 100°F or below 32°F. Do not store in a place where the humidity is above 80% or below 20%. Do not store in a place where the wood is exposed to the elements. Do not store in a place where the wood is exposed to the elements.

CREOSOTE

USE FOR CONTROL OF:
 SWELLING, SHRINKING, WARPING AND EXCESSIVE WATER
 ABSORPTION. CREOSOTE ALSO PROTECTS WOOD AGAINST
 THE RAVAGES OF INSECTS, FUNGI, AND WEATHER.

ACTIVE INGREDIENT:
 Refined Coal Tar Creosote 99.0%
 Inert Ingredient 1.0%

KEEP OUT OF REACH OF CHILDREN
WARNING
 HARMFUL OR FATAL IF SWALLOWED
 SEE SIDE PANELS FOR PRECAUTIONARY STATEMENTS

MADE BY
SEABOARD ASPHALT PRODUCTS COMPANY
 1601 Fairfield Road
 Baltimore, Maryland 21226

ONE QUART
 94633 LITERS

PRECAUTIONARY STATEMENTS
 HAZARDOUS TO HUMANS AND DOMESTIC
 ANIMALS

WARNING

FIRST AID

IF SWALLOWED: Do not induce vomiting. Give 1-2 glasses of water. If symptoms persist, call a physician.

IF ON SKIN: Wash with soap and water. If irritation persists, call a physician.

IF IN EYES: Flush with water for 15 minutes. Call a physician.

IF INHALED: Move to fresh air. If symptoms persist, call a physician.

ENVIRONMENT HAZARDS

Do not discharge into water. Do not discharge into soil. Do not discharge into air.

PHYSICAL or CHEMICAL HAZARDS

"COMBUSTIBLE."

CREO

USE FOR CONTROL OF:
 SWELLING, SHRINKING, WARPING AND EXCESSIVE WATER
 ABSORPTION. CREOSOTE ALSO PROTECTS WOOD AGAINST
 THE RAVAGES OF INSECTS, FUNGI, AND WEATHER.

ACTIVE INGREDIENT:
 Refined Coal Tar Creosote 99.0%
 Inert Ingredient 1.0%

KEEP OUT OF REACH OF CHILDREN
WARNING
 HARMFUL OR FATAL IF SWALLOWED
 SEE SIDE PANELS FOR PRECAUTIONARY STATEMENTS

MADE BY
SEABOARD ASPHALT PRODUCTS COMPANY
 1601 Fairfield Road
 Baltimore, Maryland 21226

ONE QUART
 94633 LITERS

CREOSOTE

USE FOR CONTROL OF:

SWELLING, SHRINKING, WARPING AND EXCESSIVE WATER ABSORPTION. CREOSOTE ALSO PROTECTS WOOD AGAINST THE RAVAGES OF INSECTS, FUNGI, AND WEATHER.

ACTIVE INGREDIENT:

Refined Coal Tar Creosote	99.0%
Inert Ingredient	1.0%

KEEP OUT OF REACH OF CHILDREN

WARNING

HARMFUL OR FATAL IF SWALLOWED
SEE SIDE PANELS FOR PRECAUTIONARY STATEMENTS

SEABOARD ASPHALT PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, Maryland 21226

ONE QUART
94633 LITERS

PRECAUTIONARY STATEMENTS
HAZARDOUS TO HUMANS AND DOMESTIC ANIMALS

WARNING

FIRST AID

ENVIRONMENT HAZARDS

PHYSICAL or CHEMICAL HAZARDS

"COMBUSTIBLE."

64

CREOSOTE

USE FOR CONTROL OF:

SWELLING, SHRINKING, WARPING, AND EXCESSIVE WATER ABSORPTION. CREOSOTE ALSO PROTECTS WOOD AGAINST THE RAVAGES OF INSECTS, FUNGI, AND WEATHER.

ACTIVE INGREDIENT:

Refined Coal Tar Creosote	99.0%
Inert Ingredient	1.0%

KEEP OUT OF REACH OF CHILDREN

WARNING

HARMFUL OR FATAL IF SWALLOWED
SEE SIDE PANELS FOR PRECAUTIONARY STATEMENTS

SEABOARD ASPHALT PRODUCTS COMPANY
3601 Fairfield Road
Baltimore, Maryland 21226

ONE QUART
94633 LITERS

65

BEST DOCUMENT AVAILABLE