

RAYON

"ORLON"

F

M

M

BLEACH

F

M

M

BLEACH

CAUTION  
DO NOT USE ON SILK,  
WOOL OR ACETATE.  
DO NOT USE WITH OTHER  
HOUSEHOLD CHEMICALS

NET ONE GALLON

KEEP OUT OF REACH OF CHILDREN  
READ CAUTIONS ON LABEL

ACCEPTED

2-19-71

9910-1

ACCEPTED WITH COMMENTS

DYNEL

F M

## DIRECTIONS

USE FOR WHITE AND FAST COLORS ONLY

**DO NOT USE ON SILK, WOOL OR ACETATE**

SAFE FOR DACRON, RAYON, NYLON, ORLON, AND DYNEL

**LAUNDRY**—Use 1 cup FEDMART Bleach per load in top loading washing machines; ½ cup in front loading machines; or ¼ cup per 2 gallons water.

Add bleach to regular wash water or first rinse and mix well. Wash or soak for 10 minutes. Rinse well. If clothes are already in the machine, dilute bleach before using.

**REMOVING STAINS**—Use ¼ cup bleach per quart of water.

To remove scorch, ink, fruit, tea, coffee, grass, mildew, etc., soak stained area in the solution 5 minutes. Rinse well. Repeat if necessary. Colored fabrics—test small piece before using.

**CLEANING KITCHEN & BATHROOM**—Use ¼ cup per quart of water. For cleaning sinks, bathtubs, tile, linoleum, porcelain, enameled metal, etc., spread solution with cloth. Let stand 2 minutes. Rinse well.

**TOILET BOWLS & DRAIN PIPES**—Use FEDMART Bleach full strength. Pour in bleach and swab with brush, where possible. Let stand for 10 minutes and then flush or rinse well. DO NOT use with other household chemicals.

**WHITENING AGE-YELLOWED NYLON**—Use ¼ cup per quart of water. To whiten nylon that has yellowed with age, soak the fabrics in bleach solution for 10 minutes. Rinse well. Repeat if necessary.

**USE FEDMART BLEACH IN HOUSE CLEANING TO DISINFECT, DEODORIZE AND REMOVE STAINS FROM:**

<b>REFRIGERATORS</b>	<b>WOODWORK</b>	<b>GARBAGE CANS</b>
<b>STOVES</b>	<b>WINDOWS</b>	<b>TEAPOTS</b>
<b>DRAINBOARDS</b>	<b>GLASSWARE</b>	<b>DISHES</b>
<b>FLOORS</b>	<b>PLASTIC</b>	<b>SICKROOM EQUIP.</b>

Use ¼ cup bleach per quart of water. Wash thoroughly with warm suds, then rinse. Spread solution and let stand for 5 minutes. Rinse well. Repeat on heavily stained areas if necessary.

**DO NOT USE ON SILVER, COPPER, ALUMINUM OR IRON. USE IN PORCELAIN OR ENAMEL-LINED VESSELS.**

**WARNING—NOT TO BE TAKEN INTERNALLY. UNDILUTED BLEACH MAY IRRITATE SKIN AND EYES**

**ANTIDOTE:** Internal—Feed gruel or cooked cereal followed by olive oil or cooking oil. Call a physician. External—Flood with cold water immediately. Call a physician.

**KEEP OUT OF REACH OF CHILDREN**

Active Ingredient: Sodium Hypochlorite 5.25%. Inert Ingredients: 94.75% by Weight.

Distributed by FEDMART INC.

USDA REG. NO. 9910-1

CALIFORNIA, ARIZONA AND TEXAS — HOME OFFICE: SAN DIEGO, CALIF. 92111

**ACCEPTED**

2-19-71

UNDER THE FEDERAL INSECTICIDE  
 REGULATION ACT AND THE  
 FEDERAL FOOD, DRUG AND  
 COSMETIC ACT

ESTABLISHED NO. 9910-1

Comment

# HIGH POTENCY ALGAECIDE NF

## COMPOSITION

Active ingredient  
Poly [oxyethylene (dimethyliminio) ethylene (dimethyliminio)—  
ethylene dichloride] .....60.0 percent  
Inert ingredient .....40.0 percent

## CAUTION

KEEP OUT OF THE REACH OF CHILDREN

Harmful if swallowed. Do not get in eyes. Avoid contact with skin. In case of contact flush with plenty of water for at least 15 minutes. If eye irritation persists get medical attention. Avoid contamination of food.

Rince empty container thoroughly with water and discard container. Do not reuse empty container. Destroy it by perforating or crushing. Bury or discard in a safe place away from water supplies. This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Apply this product only as specified on this label.

Net Contents 1 Gallon  
"EPA Reg. No. 9922-2"  
EPA Est. No. 9922-KS-1

10-21-74  
9922-2

DISTRIBUTED BY

# Pool and Patio

11409 WEST 89th STREET OVERLAND PARK, KANSAS 66214



## APPLICATIONS

HIGH POTENCY ALGAECIDE NF is used to control swimming pools. For maximum effectiveness, pool growth of algae should be cleaned prior to use ALGAECIDE NF.

For pools having just visible algae growth add an amount of 4 fl. oz. of HIGH POTENCY ALGAECIDE NF per 10,000 gal. of water. Remove settled algae debris by cleaning.

For treatment of a freshly cleaned and filled pool, add 4 fl. oz. of HIGH POTENCY ALGAECIDE NF per 10,000 gal. of water.

To maintain pools free of visible algae growth, substitute 4 fl. oz. of HIGH POTENCY ALGAECIDE NF per 10,000 gal. of water should be made every 5 to 7 days after the initial treatment.

Uniform distribution of HIGH POTENCY ALGAECIDE NF in the pool water is necessary for maximum effectiveness.

HIGH POTENCY ALGAECIDE NF is compatible with chlorine normally used to treat pools and is effective at both low and high chlorine levels. HIGH POTENCY ALGAECIDE NF can be used in conjunction with chlorine chemicals and may reduce the amount of chlorine normally required. However, do not mix HIGH POTENCY ALGAECIDE NF with concentrated dry or liquid chlorine products.