

ACCEPTED

**LEADWAY**

**BLEACH**

Active Ingredient: Sodium Hypochlorite 5.25% by Wt.  
Inert Ingredients 94.75% by Wt.

**CAUTION** May irritate skin and eyes (see back panel for cautions) Keep Out of Reach of Children.

safe for *NYLON ORLON DACRON*

NET 32 FL. OZ. (1 QUART)

**LEADWAY**

**BLEACH  
AND  
DISINFECTANT**

**DO NOT  
USE  
ON SILVER, WOOD  
OR BRASS**

**DIRECTIONS**

**USE FOR WHITE AND FAST COLORS**

**IN THE LAUNDRY:** Add 1/2 cup of LEADWAY bleach per each load if necessary. Mix well. Wash in usual way. As a bleach (2 gallons water or one cup LEADWAY bleach per each wash load machine). Rinse in several waters before drying. In automatic added to suds water before clothing is placed in machine. If suds, dilute with 1 quart of water before adding.

**STAIN REMOVER:** To remove scorch, ink, fruit, tea, coffee, grass of LEADWAY bleach to quart of water. Mix well and allow to stand. Rinse thoroughly.

**BATHROOM & KITCHEN:** Use 1/2 cup LEADWAY bleach per quart of water on bathtubs, tile, linoleum, porcelain, etc., spread solution with cloth well. **DO NOT** use on silverware. **TOILET-BOWLS:** Use 1/2 cup, per quart of water. Let stand for 10 minutes and then flush. **DO NOT** use with ammonia or household chemical.

**TO CLEANSE • DEODORIZE • DISINFECT:** For All surfaces in bathroom use 1/2 cup bleach per gallon of water. Wash thoroughly with warm sudsy solution with a cloth to wet surfaces thoroughly — let stand for 2 hours.

**CAUTION:** Undiluted LEADWAY bleach will irritate the skin and eyes. Call Physician. If accidentally taken internally feed bread soaked in cooking oil. Call Physician. Not for personal use.

USDA Reg. No. 200-1000

Do not use in copper, aluminum or iron vessels  
Use in porcelain or enamel lined vessels

**KEEP BOTTLE UPRIGHT IN COOL PLACE**  
**DISTRIBUTED BY NATIONAL BRANDS SALES COMPANY**  
CHICAGO, ILL. 60680

**LEADWAY**

**BLEACH**

Ingredient: Sodium Hypochlorite 5.25% by Wt.  
Active Ingredients 94.75% by Wt.

**CAUTION** May irritate skin and eyes (see back panel for cautions) Keep Out of Reach of Children.

NYLON ORLON DACRON

NET 32 FL. OZ. (1 QUART)

**LEADWAY**

**BLEACH  
AND  
DISINFECTANT**

**DIRECTIONS**

**USE FOR WHITE AND PAST COLORS ONLY**

**IN THE LAUNDRY:** Add 1/2 cup of LEADWAY bleach per each 2 gallons of water. Boiling is unnecessary. Mix well. Wash in usual way. As a bleach add 1/2 cup or 1 oz. per 2 gallons water or one cup LEADWAY bleach per each washing machine load (16 gallon machine). Rinse in several waters before drying. In automatics bleach should be added to suds water before clothing is placed in machine. If added while clothing is in suds, dilute with 1 quart of water before adding.

**STAIN REMOVER:** To remove scorch, ink, fruit, tea, coffee, grass, or other stains, add 1/4 cup of LEADWAY bleach to quart of water. Mix well and allow to soak until stains disappear. Rinse thoroughly.

**BATHROOM & KITCHEN:** Use 1/2 cup LEADWAY bleach per quart of water. To clean sinks, bathtubs, tile, linoleum, porcelain, etc., spread solution with cloth. Let stand 2 minutes. Rinse well. **DO NOT** use on silverware. **TOILET-BOWLS:** Use 1/2 cup, pour in bleach and swab with brush. Let stand for 10 minutes and then flush. **DO NOT** use with other toilet bowl cleanser, ammonia or household chemical.

**TO CLEANSE • DEODORIZE • DISINFECT:** For All surfaces in bathroom and kitchen, use 1/2 cup bleach per gallon of water. Wash thoroughly with warm suds, rinse, then spread above solution with a cloth to wet surfaces thoroughly — let stand for 2 minutes and then rinse well.

**CAUTION:** Undiluted LEADWAY bleach will irritate the skin and eyes. Rinse immediately. Call Physician. If accidentally taken internally feed bread soaked in milk followed by cooking oil. Call Physician. Not for personal use.

USDA Reg. No. [REDACTED]

Do not use in copper, aluminum or iron vessels.  
Use in porcelain or enamel lined vessel.

**KEEP BOTTLE UPRIGHT IN COOL PLACE**

**DISTRIBUTED BY NATIONAL BRANDS SALES CORP.**

CHICAGO, ILL. 60680

**DO NOT  
USE  
ON SILK, WOOL  
OR ACRYL**

ACCEPTED WITH COMMENTS

**NOTE:**

All working solutions must be adjusted to pH of approximately 4.0 prior to use, employing acetic acid (vinegar), citric acid or suitable buffer, or added to a medium which will result in a final pH of 4.0.

**DIRECTIONS FOR USE:**

**HOSPITALS, DISINFECTION:**

Walls, floors, drains, etc. - Effective against Staphylococcus aureus. Treat with 1:24 (5 1/2 fl. oz. per gallon) solution of OXODENE 20.

Bed Pans - Thoroughly cleaned bed pans may be disinfected by soaking in a 1:24 (5 1/2 fl. oz. per gallon) solution.

Fabric Disinfection - After washing, soak fabrics in a 1:24 (5 1/2 fl. oz. per gallon) solution of OXODENE 20.

**GENERAL:**

For sanitization and odor control, OXODENE 20 may be applied, after thorough cleaning, as a wash in the following:

- |                              |                        |
|------------------------------|------------------------|
| Meat Processing Plants       | Dairies                |
| Industrial Processing Plants | Food Processing Plants |
| Fish Processing Plants       | Mortuaries             |
| Poultry Processing Plants    | Boats                  |
| Poultry Hatcheries           | Flour Mills            |

Walls, floors, drains, etc. - Treat with 1:51 dilution (2 1/2 fl. oz. per gallon).

Soak soaking of previously cleaned utensils, heavily stained

dishes and glasses, equipment parts, etc. - Soak in 1:51 dilution (2 1/2 fl. oz. per gallon). Allow 20 minutes soaking period.

Flush equipment with potable water rinse before reuse.

Holding and receiving tanks - Use a 1:51 dilution (2 1/2 fl. oz. per gallon). Fill and hold for 20 minutes. Drain and flush with potable water before reuse.

Pipe Lines - Fill system with a 1:51 dilution (2 1/2 fl. oz. per gallon). Flush equipment with potable water rinse before reuse.

**MEAT PROCESSING PLANTS:**

For control of mold, mildew and bacteria -

Walls, ceilings, floors - Spray or soak with a dilution up to 1 part OXODENE 20 and 8 parts water.

For sanitization -

Cutting surfaces, utensils, equipment - Treat with 1:51 (2 1/2 fl. oz. per gallon) solution of OXODENE 20. Soak for 20 minutes. Rinse thoroughly with potable water.

**FISHING BOATS:**

After thorough cleaning, walls, decks and ceilings may be sanitized by washing with a 1:51 dilution (2 1/2 fl. oz. per gallon) of OXODENE 20. Rinse thoroughly with potable water.

**CAUTION:** Harmful if swallowed. If taken internally contact a physician. Avoid contact of concentrated material with eyes and skin. In case of contact, wash thoroughly with water. If irritation persists, contact a physician. Rinse empty container thoroughly with water and discard it.

ACC  
NOV-1  
UNDER THE  
FUNGICIDE  
FOR ECONOMIC  
UNDER NO