

PENTA DIP

redwood stain & wood preservative



**stops rot as it repels insects
water repellent**

ACTIVE INGREDIENTS:
Pentachlorophenol 4.4%
Other Chlorophenols 0.6%
INERT INGREDIENTS 95.0%
Complies with Federal
Spec. TT W 570A
EPA Reg. No. 997.1
EPA Est. No. 997.2A

DANGER! FLAMMABLE!
KEEP OUT OF REACH OF CHILDREN.
VAPOR HARMFUL. SKIN & EYE IRRITANT.
HARMFUL OR FATAL IF SWALLOWED.
see warnings on back panel.

ONE U.S. GALLON

WARNING: Call a physician if
eyes or on skin or clothing.
handling freshly treated wood.
WASH AFTER HANDLING.

This product is toxic to plants
shrubby. Keep out of reach of children.
cleaning of equipment and containers
on this label.

DANGER: FLAMMABLE
areas, provide adequate ventilation.
Close container after use.
bottles or other containers.
KEEP OUT OF REACH OF CHILDREN.

For exterior use only.
Seals — Stains — Finishes

Contains 5% Penta
insects, including termites.
Resin. PENTA DIP is a
and richness of grain.
old wood that has been
type finishes before

PENTA DIP gives a
pine, fir, redwood, eucalyptus,
fences and posts, etc.
not for treatment of

DIRECTIONS

Stir thoroughly and
requires no thinner.
to be painted is clean and dry.
brush with grain of
woods may require
before recoating.

Coverage: Approximate



STERLING-CL

9511

P

ve

S

I.
TANT.
D.

WARNING: Contains petroleum distillate. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear rubber gloves and protective clothing when handling freshly treated lumber. When spraying wear goggles and respirator.

WASH AFTER HANDLING. May be absorbed through skin and cause irritation.

This product is toxic to fish and wildlife. Keep away from pets, livestock and shrubbery. Keep out of lakes, streams and ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DANGER: FLAMMABLE: Do not use near fire or open flame. When using in confined areas, provide adequate ventilation and extinguish all open flames (pilot lights, etc.). Close container after each use. Store in cool place. Do not transfer contents to bottles or other container. Do not reuse container. Destroy when empty.

KEEP OUT OF REACH OF CHILDREN.

For exterior use only. Permanent beauty and protection.
Seals — Stains — Preserves — Protects.

Contains 5% Penta which is toxic to wood rotting organisms and wood destroying insects, including termites, powder-post beetles and ants. Reinforced with Vinyl Resin. PENTA DIP is a pigmented, penetrating stain that brings out the warm beauty and richness of grain of fine hard and soft woods. May be used on new wood or on old wood that has had other penetrating finishes that have weathered. Remove film type finishes before applying PENTA DIP.

PENTA DIP gives a rich redwood low lustre to all types of wood — cedar, mahogany, pine, fir, redwood, etc. Suitable for use on outdoor paneling, lawn and patio furniture, fences and posts, shingles, shakes, siding and many other surfaces. This product is not for treatment of wood that comes in contact with soil.

DIRECTIONS

Stir thoroughly and occasionally during application. PENTA DIP is ready to use and requires no thinner. May be applied by dip, brush, spray or roller. Be sure surface to be painted is clean and dry and free of wax, oil and grease. Flow on evenly and brush with grain of wood. A single application should be adequate; however, certain woods may require a second application. If so, allow 24 hours dry time before recoating.

Coverage: Approximately 400 sq. ft. per gallon, depending on porosity of wood.



STERLING · CLARK · LURTON CORP. MALDEN, MASS. 02148