

# COP-R DIP

## copper naphthenate wood preservative



stops rot and decay  
water repellent  
reduces paint peeling

**DANGER! KEEP OUT OF REACH OF CHILDREN.**

ACTIVE INGREDIENTS  
Copper Naphthenate 22.0%  
(Equivalent to 2.2%  
metallic copper)  
Inert Ingredients 78.0%  
100%

**COMBUSTIBLE  
HARMFUL IF SWALLOWED.**

EPA REG. NO. 9957-8  
EPA EST. NO. 9957-MA-1

#### CAUTION, COMBUSTIBLE MIXTURE

**CAUTION** Contains petroleum distillates. Harmful if swallowed. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Do not breathe vapor or spray mist. Avoid contact with skin or eyes. Wash with soap and water after handling. Do not use near fire or open flame. Avoid sparks and use in well ventilated place. Extinguish all open flames (pilot lights). Do not transfer contents to unlabeled bottles or other containers. STORAGE AND DISPOSAL. Avoid contamination of water, food and feedstuffs. To protect fish and wildlife, do not contaminate streams and ponds with this material. Open dumping is prohibited. Do not reuse empty containers. Wrap container and put in trash collection.

Liquid that cannot be used should be disposed of according to procedures approved by Federal, State or local disposal authorities.

COP-R DIP is a ready to use copper fungicide-insecticide and water repellent for use as a surface treatment on wood and cellulosic materials which may be applied by dip, brush or spray. It preserves wood against termites, rot, warping and swelling. It also preserves fabric, rope, nets and tarpaulin against mold and mildew.

**DIRECTIONS FOR USE** It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Wood to be treated should be seasoned dry. Fenceposts must have bark removed and be free of paint, wax, etc. On posts, soak 12 to 48 hours for long term protection. Pine may allow adequate penetration in 6 to 8 hours. Finished lumber and cut timbers should be soaked 15 to 30 minutes per inch of thickness.

Where COP-R DIP is applied by brushing (above ground only) generous flooding coats on all surfaces are recommended. Two applications 4 to 6 hours apart are desirable in the case of brush and spray applications for wood intended to be in contact with soil.

Treated lumber or fabric for use in proximity to growing plants should be allowed to dry thoroughly before being used.

COP-R DIP imparts a light green color to wood which is not a stain, but simply the color of the fungicide. The characteristic green color gives visual evidence of treatment and protection. The color will not show or bleed through succeeding coats of paint or enamel. Do not use latex paint over COP-R DIP until thoroughly cured.

**COVERAGE** Approximately 300-400 square feet per gallon depending on wood porosity and surface conditions.

Clean hands, tools and brushes with paint thinner.

Complies with existing air pollution control regulations.


KEEP OUT OF REACH OF CHILDREN

STERLING-CLARK LUITON CORP.  
MALDEN, MASS. 02148

5 U.S. GALLONS

# COP-R DIP

**copper naphthenate  
wood preservative**



**stops rot and decay  
water repellent  
reduces paint peeling**

**DANGER! KEEP OUT OF REACH OF CHILDREN.**

Active Ingredients  
Copper naphthenate  
(Equivalent to 2.2%  
metallic copper)  
Inert Ingredients

22%

78%

100%

**COMBUSTIBLE.  
HARMFUL IF SWALLOWED.  
see cautions on back panel.**

EPA Reg. No. 9957-8  
EPA Est. No. 9957-MA-1

**ONE U.S. QUART**

## COP-R DIP wood preservative

COP-R DIP is a ready to use copper fungicide-insecticide and water repellent for use as a surface treatment on wood and cellulosic materials which may be applied by dip, brush or spray. It preserves wood against termites, rot, warping and swelling. It also preserves fabric, rope, nets and tarpaulin against mold and mildew.

**INSTRUCTIONS FOR USE.** It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Wood to be treated should be seasoned dry. Fenceposts must have bark removed and be free of paint, wax, etc. On posts, soak 12 to 48 hours for long term protection. Pine may allow adequate penetration in 6 to 8 hours. Finished lumber and cut timbers should be soaked 15 to 30 minutes per inch of thickness.

Where COP-R DIP is applied by brushing (above ground only) generous flooding coats on all surfaces are recommended. Two applications 4 to 6 hours apart are desirable in the case of brush and spray applications for wood intended to be in contact with soil. Treated lumber or fabric for use in proximity to growing plants should be allowed to dry thoroughly before being used.

COP-R DIP imparts a light green color to wood which is not a stain, but simply the color of the fungicide. The characteristic green color gives visual evidence of treatment and protection. The color will not show or bleed through succeeding coats of paint or enamel. Do not use latex paint over until thoroughly cured.

Approximately 300-400 square feet per gallon depending on wood porosity and surface conditions.


Clean hands, tools and brushes with paint thinner

Complies with existing air pollution control regulations.

Contains petroleum distillates. Harmful if swallowed. If swallowed, do not induce vomiting. Do not breathe vapor or spray mist. Avoid contact with skin or eyes. Wash with soap and water after handling. Do not use near fire or open flame. Avoid sparks and use in well ventilated place. Extinguish all open flames (pilot lights). Do not transfer contents to unlabeled bottles or other containers.

Avoid contamination of water, food and feedstuffs. To protect fish and wildlife, do not contaminate streams and ponds with this material. Open dumping is prohibited. Do not reuse empty containers. Wrap container and put in trash collection.

Liquid that cannot be used should be disposed of according to procedures approved by Federal, State or local disposal authorities.



STERLING CLARK LORTON CORP. MALDEN MASS 02148