## PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive may cause severe skin irritation or chemical burns to broken skin. Causes eye damage. Do not get in eyes, on skin or on ctothing. Wear goggles or face shield and rubber gloves when handling this product. Wash after handling. Avoid breathing vapors. Vacate poorly ventilated areas as soon as possible. Do not return until odors have dissipated.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes streams or ponds. Treated effluent may not be discharged into lakes, streams, ponds or public waters without a valid discharge permit. For guidance contact the regional office of the Environmental Protection Agency.

#### PHYSICAL AND CHEMICAL HAZARDS: STRONG OXIDIZING AGENT: Mis only with

water according to label directions. Mixing this product with gross filth such as feces urine etc. or with ammonia acids delergents or other chemicals may release hazardous gases irritating to eyes lungs and mucous membranes.

manufactured by

EXSL CHEMICAL CO. 630 WALSH AVE SANTA CLARA CA 95050

EPA REG. NO EPA EST. NO. 09987-CA-01 NET CONTENTS

### LTM - SAN LIQUID SANITIZER

# LOW TEMPERATURE MECHANICAL WASHER SANITIZER FOR INDUSTRIAL USE ONLY

## DANGER

FIRST AID: If on skin, wash with plenty of soap and water if in eyes, flush with water for at least 15 minutes. Get medical attention it swallowed drink large quantities of milk, or getatin solution or if these are not available, drink large quantities of water. Do NOT give vinegar or other acids. Do NOT induce vomiting. Get prompt medical attention.

See additional precautions on side panel

### DIRECTIONS FOR USE GENERAL CLASSIFICATION

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

AVAILABLE CHLORINE TABLE OF PROFORTIONS

50 ppm - 1 oz per 12 gals v/ate<sup>2</sup> = 100 ppm - 2 oz per 12 gals water<sup>2</sup> = 200 ppm - 4 oz per 12 gals water

FOR SANITIZING TABLEWARE in low-temperature warewashing machines, inject Sani-Clean into the final rinse water at a concentration of 100 ppm available chlorine. Do not exceed 200 ppm. Air Jry

#### DO NOT USE ON SILVER AND SILVER PLATE

To insure that available chlorine concentration does not fall below the 50 ppm, periodically test the rinse solution with a suitable test kit and adjust the dispensing rate accordingly Consult your local Ware Washing Specialist for technical assistance and further information on sanitizing tableware in warewashing machines.

#### FOR INDUSTRIAL USE ONLY DO NOT MIX WITH ANYTHING BUT WATER

NOTE: This product degrades with age. Use a chlorine test kit and increase dosage as necessary to obtain the required level of available chloring.

STORAGE AND DISPOSAL: Store in a cool dr, area away from direct sunlight. In case of spill flood area with rarge quantities of water. Rinse empty container thoroughly with water and either return to manufacturer or discard by placing in trash collection or burying in an approved land ill. Product or rinsate that cannot be used should be diluted with water and disposed of in a sanitary sewer. Do not contaminate food or feed by storage, disposal or cleaning of equipment.